DATASHEET - EU8E-SWD-8XD-1

SWD Block module I/O module IP69K, 24 V DC, 8 outputs with separate power supply, 8 M12 I/O sockets

Part no. **EU8E-SWD-8XD-1**
183274

General specifications	
Product name	Eaton EU8E Digital module
Part no.	EU8E-SWD-8XD-1
EAN	4015081782079
Product Length/Depth	34 millimetre
Product height	212.6 millimetre
Product width	61.6 millimetre
Product weight	0.32 kilogram
Certifications	CSA UL IEC/EN 61131-2
Product Tradename	EU8E
Product Type	Digital module
Product Sub Type	None
Catalog Notes	with supply
Features & Functions	
Electric connection type	Screw connection
Features	Overload proof (with diagnostics) Overload protection (sensor supply) Fieldbus connection over separate bus coupler possible Short-circuit protection (sensor supply)
Functions	For connection of digital I/O signals Short-circuit protection, outputs available
General information	
Current consumption	79 mA, SmartWire-DT network, 24 V, without sensor and without I/O supply 70 mA, Max. current consumption per M12 I/O plug, Sensor supply, SmartWire-DT network
Degree of protection	IP69K
Overvoltage category	II
Pollution degree	3
Product category	SmartWire-DT slave
Residual ripple	≤ 5 % (input voltage)
Type	Digital modules
Voltage type	DC
Ambient conditions, mechanical	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	30 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions	Condensation: permissible

Operating temperature - min	-25 °C
Operating temperature - max	55 °C
Relative humidity	5 - 95 % (non-condensing, IEC/EN 60068-2-30)
Electro magnetic compatibility	
Air discharge	8 kV, according to IEC 61131-2, level 3, ESD
Burst impulse	2 kV, Supply cable, according to IEC/EN 61131-2, Level 3 1 kV, Signal cable, according to IEC/EN 61131-2, Level 3 1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3
Contact discharge	4 kV, according to IEC/EN 61131-2, Level 2, ESD
Electromagnetic fields	1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008)
Radiated RFI	10 V (IEC/EN 61131-2:2008, Level 3)
Radio interference class	Class A (EN 55011)
Surge rating	1 kV, Surge I/O cables, Surge (IEC/EN 61131-2:2008, Level 1), EMC 0.5 kV, Surge power cables, Surge (IEC/EN 61131-2:2008, Level 1), EMC
Electrical rating	
Input current at signal 1	0 mA
Output current	0.5 A
Power loss	1.7 W
Rated operational voltage	24 V DC (-15 %/+ 20 % - power supply)
Short-circuit tripping current	Max. 1.2 A over 3 ms, Digital semi-conductor outputs
Supply voltage at AC, 50 Hz - min	0 V AC
Supply voltage at AC, 50 Hz - max	0 V AC
Supply voltage at DC - min	20.4 V DC
Supply voltage at DC - max	28.8 V DC
Communication	
Connection to SmartWire-DT	Yes
Connection type	SWD-IN : M12 plug (A-keyed), 5 pole 5-pin M12 socket (A-keyed), Supply and I/O sensor SWD-OUT: M12 socket (A-keyed), 5 pole
Data transfer rate	Setting automatically 2 MBit/s, SmartWire-DT
LED indicator	Status indication of display outputs: Yellow LED Status indication of SmartWire-DT network: Green LED
Protocol	Other bus systems
Station	SmartWire-DT slave, SmartWire-DT network
Input/Output	
Lamp load	≤ 3 W (at RLL)
Number of inputs (digital)	0
Number of outputs (digital)	8
Output	8 Transistor Outputs
Switching capacity	IEC/EN 60947-5-1, utilization category DC-13, Digital outputs
Safety	
Explosion safety category for dust	None
Explosion safety category for gas	None
Potential isolation	Outputs to SmartWire-DT: yes
Protection against polarity reversal	Yes
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	1.7 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - digital I/O module (EC001599)			
Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Field bus, decentralized peripheral / Field bus, decentralized peripheral - digital I/O module (ecl@ss13-27-24-26-04 [BAA055019])			
Supply voltage AC 50 Hz		V	0 - 0
Supply voltage AC 60 Hz		V	0 - 0
Supply voltage DC		V	20.4 - 28.8
Voltage type (supply voltage)			DC
Number of digital inputs			0
Number of digital outputs			8
Digital inputs configurable			No
Digital outputs configurable			No
Input current at signal 1		mA	0
Permitted voltage at input		V	20.4 - 28.8
Type of voltage (input voltage)			DC
Type of digital output			Other
Output current		A	0.5
Permitted voltage at output		V	20.4 - 28.8
Type of output voltage			DC
Short-circuit protection, outputs available			Yes
Number of HW-interfaces industrial Ethernet			0
Number of interfaces PROFINET			0
Number of HW-interfaces RS-232			0
Number of HW-interfaces RS-422			0
Number of HW-interfaces RS-485			0
Number of HW-interfaces serial TTY			0
Number of HW-interfaces parallel			0
Number of HW-interfaces wireless			0
Number of HW-interfaces USB			0
Number of HW-interfaces other			0
With optical interface			No
Supporting protocol for EtherCAT			No
Supporting protocol for TCP/IP			No
Supporting protocol for PROFIBUS			No
Supporting protocol for CAN			No
Supporting protocol for INTERBUS			No

Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP69K
Type of electric connection		Screw connection
Time delay at signal change	ms	0.2 - 0.2
Fieldbus connection over separate bus coupler possible		Yes
Rail mounting possible		No
Wall mounting/direct mounting		Yes
Front built-in possible		No
Rack-assembly possible		No
Suitable for safety functions		No
SIL according to IEC 61508		None
Performance level according to EN ISO 13849-1		None
Appendant operation agent (Ex ia)		No
Appendant operation agent (Ex ib)		No
Explosion safety category for gas		None
Explosion safety category for dust		None
Certified for UL hazardous location class I		No
Certified for UL hazardous location class II		No
Certified for UL hazardous location class III		No
Certified for UL hazardous location division 1		No
Certified for UL hazardous location division 2		No
Certified for UL hazardous location group A (acetylene)		No
Certified for UL hazardous location group B (hydrogen)		No
Certified for UL hazardous location group C (ethylene)		No
Certified for UL hazardous location group D (propane)		No
Certified for UL hazardous location group E (metal dusts)		No
Certified for UL hazardous location group F (carbonaceous dusts)		No
Certified for UL hazardous location group G (non-conductive dusts)		No
Width	mm	61.6
Height	mm	212.6
Depth	mm	34

© 04/2023 by Eaton Industries GmbH