CAT. N° 0 266 86



ROTARY HANDLE VARI-DEPTH IP55 - DPX-IS 250/630 FRONT AND SIDE HANDLE

Pack (number of units)	1
Volume (dm³)	2,35
Weight (g)	511,00

Product characteristics

Rotary handles

Vari-depth handle IP 55

- Comprising: connecting rod, bracket, self-adhesive drilling template, fixing accessories (seal to maintain the IP protection up to IP 55, door lock mechanism)
- For front and side handle device

General characteristics

DPX™-IS 630 isolating switches - 400 to 630 A

- Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts
- Padlock integrated in the handle
- Supplied with terminal shields, and cage terminals
- Conform to IEC 60947-3
- Category of use AC 23 A
- Accept electrical auxiliaries
- Can be mounted on plate in XL³ enclosures

Documentation

Catalogue pages & additional information

- Description page (p.167)
- Description page (p.168)
- Technical page (p.170)
- DPXTM-IS 250 isolating switches
- DPXTM-IS 630 isolating switches

Installation instructions & related documents

- LE04940AB
- Y0299A

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.