PRODUCT-DETAILS

E4.2V 4000 Ekip Touch LI 3p F HR

E4.2V 4000 Ekip Touch LI 3p F HR



General Information

Extended Product Type	E4.2V 4000 Ekip Touch LI 3p F HR
Product ID	1SDA071224R1
EAN	8015644750749
Catalog Description	E4.2V 4000 Ekip Touch LI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E4.2V 4000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LI R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1904 9AKK108468A1910

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	104d4b83-8055-4340-a90b-594733d22d27 Italy (IT)
Simplified SCIP	5bbce6f9-a277-4a48-98f0-8af6e65a877c Germany (DE) c907ad59-1137-42ae-b1ef-a9b864817ebc Sweden (SE) 9bba3fe5-9a14-4324-82f8-864493564e99 Poland (PL) e7bc7b91-6dc6-4f7e-80d6-2fb2673d3ece Greece (GR) 3b9ec31e-414c-47ac-b736-49e6e663890b Estonia (EE) b0bda8b4-7865-468e-9bab-462dd5b3aa26 Hungary (HU) a47cb2bf-5f11-4c76-8661-e59b487d48b5 Netherlands (NL) 67fc5b32-4347-4f66-bec7-9cfe6178fcf3 Poland (PL) a2388151-03b4-432c-8943-789062cda78c Spain (ES) 5630d34f-c285-4aa8-9035-5b63548eacb0 Belgium (BE) 1698aea2-9331-4415-8658-6643e18093e7 Germany (DE) e3c7f928-7a30-4135-ab60-88e533ce6438 Finland (FI) 43197ecf-1861-446c-8377-69c01925d7d3 France (FR) a186452b-2307-4dd9-8d75-72b4aa041055 Poland (PL) f7ad0f33-e718-4f18-bdf0-ee51c1e9ada5 Norway (NO) 8b40bc07-f613-4fd2-a588-4a0cf06a2e86 Czech Republic (CZ) 1c16b4a8-64ea-4723-9239-94855d517430 Belgium (BE) cdd21245-50cd-4785-a91f-81a8c7b11dbc Croatia (HR) 6b1cb39a-a14d-4d6d-af10-09d80c3c014e Sweden (SE) 50ce231f-6142-4f4c-b116-8f8dd76d6eaf Germany (DE) 17e807fb-c94d-46ab-b9ee-2662f39c385c Germany (DE) 638cadbe-32fb-4d8b-8dc0-8ff55e404400 Hungary (HU) cf33c91b-adc7-4fab-8a1a-7dc8ab66fd87 Germany (DE) be4eaf20-bda9-4688-b8f4-d0a081f7e086 France (FR) 4c53c372-e33a-4a83-aa80-6dfe2539c263 Portugal (PT) 86dae21e-2dbb-4f09-857f-19e66ed51c00 Denmark (DK) 2ad7075a-98e0-406f-83a0-c3b2cd254034 Bulgaria (BG)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	Z4VWERBD000A000000XX
EAN	8015644750749
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	384 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	56 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	63 kg
Package Level 1 EAN	8015644750749

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0171

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 5000 cycle Ue = 500 ... 690 V 4000 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3P
Power Loss	465 W
Rated Current (I_n)	4000 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	4000 A
Rated Voltage (U_r)	690 V
Recommended Screw	Main Circuit M12

© 2024 ABB. All rights reserved.

Driver	
Release	Ekip Touch LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E4.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5545
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001001R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.