# 4902 - FEMALE/FEMALE BSP PARALLEL




| | |
|---|---|
| **maximum working pressure** | 30 bar<br>3 MPa<br>435 psi |
| **working temperature** | -20 to 130 °C<br>-4 to 266 °F<br>253 to 403 °K |
| **body** | NICKEL PLATED BRASS |
| **retaining nut** | NICKEL PLATED BRASS |
| **stem** | NICKEL PLATED BRASS |
| **stem seal** | PTFE |
| **'O'-rings** | PTFE |
| **ball seal** | PTFE |
| **handle** | TREATED STEEL |

• Convert to inch • Convert to oz • Reset Filters

| Part Nb | C | E (mm) | F (mm) | H (mm) | L (mm) | M (mm) | (kg) |
|---|---|---|---|---|---|---|---|
| | All | All | All | All | All | All | All |
| 4902 01 45 | G4 | 29 | 125 | 154 | 191 | 255 | 9.04 |
| 4902 10 13 | G1/4 | 9 | 20 | 38 | 39 | 82 | .131 |
| 4902 10 17 | G3/8 | 9 | 20 | 38 | 39 | 82 | .117 |
| 4902 15 21 | G1/2 | 11 | 25 | 43 | 50 | 100 | .204 |
| 4902 20 27 | G3/4 | 12 | 31 | 50 | 54 | 120 | .329 |
| 4902 25 34 | G1 | 14 | 38 | 54 | 67 | 120 | .468 |
| 4902 32 42 | G1 1/4 | 15 | 48 | 73 | 77 | 158 | .77 |
| 4902 40 49 | G1 1/2 | 17 | 54 | 79 | 90 | 158 | 1.04 |
| 4902 50 48 | G2 | 19 | 66 | 86 | 106 | 158 | 1.76 |
| 4902 65 47 | G2 1/2 | 22 | 85 | 132 | 136 | 255 | 4.5 |
| 4902 80 46 | G3 | 25 | 99 | 140 | 157 | 255 | 5.84 |