Specifications

Eaton 181629

Catalog Number: 181629

Eaton Moeller® series C22 Illuminated pushbutton actuator, maintained, green, 24 V, 1 N/O, with cable 0.5m and M12A plug



General specifications

Product Name
Eaton Moeller® series C22 Illuminated pushbutton actuator

Catalog Number
181629

EAN
4015081764969

Product Length/Depth
560 mm

Product Height
30 mm

Product Width
30 mm

Product Weight
0.05 kg

Certifications
CSA
UL 508
UL
CSA Class No.: 321103
UL File No.: E29184
VDE 0660
CSA-C22.2 No. 14-05 and 94-M91
IEC/EN 60947-5-1
CSA File No.: 165628
UL Category Control No.: NKCR
CE
CSA-C22.2 No. 14-18 and No. 94.2-15
CE marking

Powering Business Worldwide

Product specifications

Type

Illuminated pushbutton actuator

Actuator color

Green

Actuator function

Maintained

Switching function latching

Electric connection type

Other

Fitted with:

Front ring

Operating frequency

3600 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT

No

Rated impulse withstand voltage (Uimp)

800 V AC

Bezel color

Titanium

Cable material

PUR

Actuating force

5 N

Actuator diameter

29.7 mm

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-30 °C

Lamp voltage - max

24 V

Resources

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004157.pdf

DA-DC-00004135.pdf

Drawings

eaton-operating-c22-pushbutton-dimensions-002.eps

eaton-operating-button-symbol-004.eps

eaton-operating-pushbutton-3d-drawing-002.eps

eCAD model

DA-CE-ETN.C22-DRL-G-K10-24-P3

Installation instructions

IL047016ZU

Installation videos

Eaton's RMQ compact solution pilot devices

mCAD model

DA-CD-c22_d_m12a_4pol

DA-CS-c22_d_m12a_4pol

Sales notes

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

System overview

Pilot devices - selection aid

Wiring diagrams

eaton-operating-wiring-diagram-004.eps

Number of command positions

1

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

1

Bezel material

Plastic

Design

Flat

M12A

Classical

Mounting position

As required

Light color

Green

Rated conditional short-circuit current (Iq)

1 kA

Connection type

Cable (black) with M12A plug, 4 pole

Cable length

0.5 m

Overvoltage category

III

Control circuit reliability

1 failure per 17,000,000 swtching operations (statistically determined, at 17 V DC/7 mA: N/O contact

Degree of protection

NEMA 12

IP67/IP69K

Inscription

Blank

Front element type

Flat

Lens type

Round

Rated operational voltage

24 V AC/DC (LED)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Lifespan, mechanical

1,000,000 Operations (AC operated)

Short-circuit protection rating

Max. 4 A gG/gL, Fuse, Contacts

Opening diameter

22.5 mm

Opening height

0 mm

Rated insulation voltage (Ui)

250 V

Rated operational current (Ie) at AC-15, 24 V

4 A

Rated operational current (Ie) at DC-13, 24 V

3 A

Width opening

0 mm

Product category

RMQ compact solution

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

30 °C

Tightening torque

2 Nm, Threaded ring

1 Nm, Plug

Suitable for

Illumination



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia