Rittal – The System.

Faster – better – everywhere.

Security lock – SZ 2419.000

Date : Apr 27, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Security lock – SZ 2419.000

created: 27.04.2021 build on www.rittal.com/uk-en



Product description

Description:	Fitted to doors, to protect against contact with live electrical equipment whilst the master switch is ON.
Function principle:	Locks the door when the master switch is ON. Mains power (voltage) is only enabled whilst the door is closed. Monitoring of the lock magnet via an additional closing contact.
Assembly instruction:	In two-door enclosures, the door-operated switch is required for the overlapping door, to indicate "enclosure door closed"
Supply includes:	Lock Actuator Angle bracket Assembly parts

Product description

To fit:	Enclosure type: VX Enclosure type: TS Enclosure type: SE
Rated operating voltage:	120 V
Power consumption:	At 50 Hz: 8 VA At 60 Hz: 8 VA
Rated insulation voltage:	400 V AC
Rated impulse withstand voltage, phase to phase:	4000 V AC

Packs of:	1 pc(s).
Weight/pack:	0.74 kg
Copper weight (kg per piece):	0
EAN:	4028177022713
Customs tariff number:	83015000
ETIM 7.0:	EC002626
ETIM 6.0:	EC002626
eCl@ss 8.0/8.1:	27189266
eCl@ss 6.0/6.1:	27189266
Product description:	SZ Security lock, 120 V AC

Approvals

Approvals:	CSA UL
Certificates:	EAC
Declarations:	Declaration of conformity