P2MB2PC100

MINIATURE CIRCUIT BREAKER, 1P, 2P, 3P AND 4P - 10KA, CHARACTERISTIC C, 100A



Product designation			Miniature circuit breaker (MCB)
Product type designation			P2 MB
Number of poles			2P
Number of DIN modules			3
Compliance			IEC / UL1077
Electrical features			
Rated insulation voltage Ui IEC/EN		V	400
Rated impulse withstand voltage Uimp		kV	6
Rated operational voltage AC (IEC)		VAC	230/400
Rated operational voltage DC		VDC	125
Rated frequency		Hz	50/60
Rated current (In)		A	100
Tripping curve			C
Short circuit rating (IEC)		kA	10
Electrical life		cycles	10000
Power dissipation per pole max		W	14
Ambient conditions			
Operating temperature			
	min	°C	-40
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+80
Max altitude		m	2000
Mechanical features			
Operating position			
	normal		Vertical plan
Fixing			35mm DIN rail
Tightening torque for terminals			
	min	Nm	3.2
	max	Nm	3.5
	min	lbin	28.3
	max	lbin	31
Terminals tool			Pz 2
Conductor section			
IEC			
	min	mm²	2.5
	max	mm²	50
AWG/Kcmil			
	min		14
	max		1/0
Mechanical life		cycles	10000
Weight		g	340
Frontal IP degree			IP20

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Pollution degree	3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance	
	CSA C22.2 n°235. UR "UL Recognized" per Canada e USA.
	IEC/EN 60947-2
	UL 1077
Certifications	
	cURus
	EAC
	TÜV-Rheinland

ETIM classification

ETIM 8.0	EC000042 - Miniature circuit breaker (MCB)

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding