Rittal – The System.

Faster – better – everywhere.

Optipanel – CP 6380.040

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Optipanel – CP 6380.040

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Design:	Support arm connection, rectangular 120 x 65 mm
Benefits:	Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material:	Enclosure: Extruded aluminium section Corner pieces: Die-cast zinc Corner protectors: Plastic
Colour:	Enclosure: Natural anodised. Corner pieces: RAL 7035 Corner protectors: similar to RAL 7024
Protection category IP to IEC 60 529:	IP 65
Supply includes:	Enclosure with hinged rear panel Seals
Note:	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Hinging of the rear panel on the longest enclosure side
Basic material:	Aluminium

Product description

For the configuration of subracks:	To fit front panel width: 482.6 mm

Installation depth:	100 mm
To fit front panels:	with width: 482.6 mm with height: 354.8 mm
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	6.6 kg
EAN:	4028177429093
Customs tariff number:	94032080
ETIM 7.0:	EC002504
ETIM 6.0:	EC002504
eCl@ss 8.0/8.1:	27180505
eCl@ss 6.0/6.1:	27180505
Product description:	CP Optipanel, for front panel BH 482,6x354,8 mm, installation depth 100 mm, Extruded aluminum section, Support arm connection 120x65 mm

Approvals

Approvals:	UL + C-UL
Certificates:	Protection category
Declarations:	Declaration of conformity