# DATASHEET - IZMX-LCS-1

**Signalling switch ready to switch-on, 1W**

| | |
|---|---|
| **Part no.** | **IZMX-LCS-1** |
| | **184104** |
| **EL Number (Norway)** | **4398467** |

## General specifications

| | |
|---|---|
| Product name | Eaton Moeller series IZMX/INX auxiliary contact block |
| Part no. | IZMX-LCS-1 |
| EAN | 4015081783120 |
| Product Length/Depth | 100 millimetre |
| Product height | 100 millimetre |
| Product width | 100 millimetre |
| Product weight | 0.023 kilogram |
| Compliances | RoHS conform |
| Product Tradename | IZMX/INX |
| Product Type | Accessories |
| Product Sub Type | Auxiliary contact block |

## Delivery program

| | |
|---|---|
| Type | Accessory |
| Model | Integrable |
| Special features | OFF message<br>The retrofit kit includes the required SEC control cable terminals.<br>For signaling availability. Alternatively, also for automatic closing upon availability.<br>1 changeover contact |
| Used with | IZMX16..., IZMX40...<br>INX16..., INX40... |

## Technical Data - Electrical

| | |
|---|---|
| Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V | 10 A |
| Rated breaking capacity (inductive load) | 0.5 A (125 V DC)<br>10 A (250 V AC)<br>0.25 A (250 V DC) |
| Electric connection type | Flat plug-in connection |

## Technical Data - Mechanical

| | |
|---|---|
| Mounting Method | Other |
| Number of contacts (change-over contacts) | 1 |
| Number of contacts (normally closed contacts) | 0 |
| Number of contacts (normally open contacts) | 0 |
| Number of switches (fault signal) | 0 |
| Lamp holder | None |

## Design verification as per IEC/EN 61439 - technical data

| | |
|---|---|
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |

## Additional information

| | |
|---|---|
| Accessory/spare part type | Auxiliary contact |

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])

| | | |
|---|---|---|
| Number of contacts as change-over contact | | 1 |
| Number of contacts as normally open contact | | 0 |
| Number of contacts as normally closed contact | | 0 |
| Number of fault-signal switches | | 0 |
| Rated operation current Ie at AC-15, 230 V | A | 10 |
| Type of electric connection | | Flat plug-in connection |

| | | | |
|---|---|---|---|
| Model | | | Integrable |
| Mounting method | | | Other |
| Lamp holder | | | None |


© 04/2023 by Eaton Industries GmbH