Specifications

Eaton 286701



Catalog Number: 286701

Eaton xEnergy Basic LV systems Low voltage switchgear. Top/Bottom-panel for Surface-Mounting Installation distribution board, with cut-out for cable entry, WxD=600x249mm

General specifications

Product Name
Eaton xEnergy Basic LV systems Low voltage switchgear

Catalog Number
286701

EAN
4015082867010

Product Length/Depth
265 mm

Product Height
75 mm

Product Width
615 mm

Product Weight
2.56 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Used with

Service distribution board IVS

Accessory consideration

Accessory

Wall-mounting distribution system

Special features

Pair (for top and bottom),

incl. screws

With aperture for cable entry

With opening for cable entry

Type

Additional equipment for wall-mounted service distribution board IVS

Accessory/spare part type

Bottom plate

Roof plates

Fitted with:

Cable entry

Surface finishing

With powder coating

Powder coating

Cable entry type

Open

Color

Light gray (RAL 7035)

Gray

Degree of protection

IP30

Unit type

Modular system

RAL-number

7035

Suitable for enclosure building length/depth

249 mm

Suitable for enclosure building width

600 mm

Suitable for length/depth

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_xEnergy_Basic_BP

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

249 mm

Suitable for width

600 mm

Material

Steel

Housing material

Sheet steel

Mounting method

Surface mounting

Suitable for

Bottom planking

Roof planking

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia