PSEN me5M NC-NC-NC.NC 1switch 6L000011



Mechanical safety gate system PSENmech, interlock principle magneticforce, contacts interlocking 3 N/C, contacts guard locking 1 N/C, supplyvoltage 24 V AC/DC.

Technical details

General data	
Approval:	CSA, CE, CCC, UKCA, DGUV
Suitable for series connection:	ja
unit type:	Sensor
Technical data	
Electrical data	
Supply voltage (V):	24
Type of supply voltage U1:	AC/DC
Relay outputs	
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	250
Max. current AC15 safety cont.:	1.5
Voltage DC13 safety cont.:	250
Environmental data	
Ambient temperature:	-25
Overvoltage category:	II
Protection type, housing:	IP67
Mechanical data	
Holding force:	1500
Height dimension:	192

Width dimension:	42
Depth dimension:	44
Net weight:	489
Gross weight:	541
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACh compliance:	Contains no SVHC substances
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122205
EAN-Code:	4046548101409
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593
Volume:	1.258 dm3

Optional accessories



6L000006 PSEN me5 20mm extension



6L000007 PSEN me5 40mm extension

	6L000008	PSEN me5 emergency release front
	6L000009	PSEN me5 emergency release back
	6L000005	PSEN me5 escape release
	570793	PSEN cable 200m-8x0.25mm²