Rittal – The System.

Faster – better – everywhere.

# Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7712.135

Date : Apr 27, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7712.135

created: 27.04.2021 build on www.rittal.com/uk-en



## Product description

| | |
|---|---|
| **Design:** | with punched rails and mounting angles, depth-variable |
| **Description:** | Wall-mounted enclosure with optimum accessibility due to hinged part. |
| **Material:** | Wall and hinged part: Sheet steel, 1.5 mm<br>Viewing window: Single-pane safety glass, 3 mm |
| **Surface finish:** | Powder-coated |
| **Colour:** | Wall and hinged part: RAL 7035<br>Glazed door: RAL 7035/7015 (slate grey) |
| **Protection category IP to IEC 60 529:** | IP 55 |
| **IK Code:** | IK08 |
| **Supply includes:** | Wall section with solid gland plate, top and bottom, two vertical mounting rails and C rail, horizontal, for cable clamping<br>Hinged part with 25 mm pitch pattern of holes in the front and rear frame, and two 482.6 mm (19") mounting angles at the front, infinitely depth-variable<br>4 wall mounting brackets 10 mm<br>Designer glazed door<br>1 double-kit key no. 5<br>Mini-comfort handle for lock inserts<br>Security lock 3524 E |
| **Basic material:** | Sheet steel |

## Product description

| | |
|---|---|
| **Dimensions:** | Width: 600 mm<br>Height: 612 mm<br>Units: 12 U<br>Depth: 473 mm |
| **Depth hinged part:** | 316 mm |
| **Installation depth:** | 420 mm |
| **Clearances:** | Clearance width: 502 mm<br>Clearance height: 549 mm |
| **Wall section:** | Depth: 135 mm |
| **Load capacity:** | Hinged part, static (max.): 600 N |
| **Packs of:** | 1 pc(s). |
| **Weight/pack:** | 36 kg |
| **EAN:** | 4028177324190 |
| **Customs tariff number:** | 94032080 |
| **ETIM 7.0:** | EC000261 |
| **ETIM 6.0:** | EC000261 |
| **eCl@ss 8.0/8.1:** | 27142408 |
| **eCl@ss 6.0/6.1:** | 27180208 |
| **Product description:** | DK Wall-mounted enclosures, 3-part, WHD: 600x612x473 mm, 12 U, With punched rails, and mounting angles, depth-variable |

## Approvals

| | |
|---|---|
| **Approvals:** | UL + C-UL |
| **Certificates:** | IK-Code<br>NA<br>Protection category |