# DATASHEET - KLV-SF4HWP-4PR

**Hollow wall expansion kit with plug-in terminal 4 row; form of delivery for projects**

**Part no.** **KLV-SF4HWP-4PR**
**178861**

| | |
|---|---|
| **General specifications** | |
| Product name | Eaton xComfort KLV project delivery form |
| Part no. | KLV-SF4HWP-4PR |
| EAN | 4015081741908 |
| Product Length/Depth | 40 millimetre |
| Product height | 715 millimetre |
| Product width | 360 millimetre |
| Product weight | 3.38 kilogram |
| Compliances | RoHS conform |
| Certifications | IEC/EN 62208, IEC/EN 60670-24 (PD) |
| Product Tradename | xComfort KLV |
| Product Type | Project delivery form |
| Product Sub Type | None |
| **Delivery program** | |
| Type | Basic device Installation distribution boards KLV for projects |
| Accessory/spare part type | Accessory<br>Other |
| Application | Indoor (installation site) |
| Color | Traffic white (RAL 9016) |
| **Technical Data - Electrical** | |
| Frequency rating | 50 Hz |
| **Technical Data - Mechanical** | |
| Mounting method | Hollow wall |
| Material | Polystyren (plastic)<br>Sheet steel, powder-coated |
| Degree of protection | IP30<br>IK05 (impact resistance) |
| Number of module space units per row | 12 |
| Number of rows | 4 |
| Terminal type | Plug-in terminals |
| PE and N terminal number and cross section | PE: 4 x (2.5 $mm^2$ - 25 $mm^2$) + 28 x (0.5 $mm^2$ - 4 $mm^2$)<br>N: 4 x (2.5 $mm^2$ - 25 $mm^2$) + 28 x (0.5 $mm^2$ - 4 $mm^2$) |
| Cover/door color | White |
| Installation type | Hollow-wall mounting |
| Module rack type | Rail frame |
| Protective shrouding material | Plastic |
| **Design verification as per IEC/EN 61439 - technical data** | |
| Ambient operating temperature details | -5 °C - 40 °C |
| **Additional information** | |
| Fitted with: | Device support rails<br>Cable retainer<br>Installation instructions<br>Imprintable sheet<br>Front cover<br>3D adjustment element for mounting<br>Neutral-/protective conductor terminal |
| Functions | Additional equipment<br>Basic device |
| Protection class | II (totally insulated) |
| Special features | IP30 Protection Class II Sheet steel door, white (RAL 9016) |
| Used with | Installation distribution boards<br>KLV for projects |

| | | | |
|---|---|---|---|
| | | | Basic device |

## Technical data ETIM 9.0

| | | | |
|---|---|---|---|
| Distribution boards (EG000023) / Accessories/spare parts for small distribution board (EC002287) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Electrical distribution system (including small distribution board, accessories) (ecl@ss13-27-14-24-92 [AFR782008]) | | | |
| Type of accessory/spare part | | | Other |
| Accessory | | | Yes |
| Spare part | | | No |


© 04/2023 by Eaton Industries GmbH