Date: 10/04/2023

S-11 ; -1 ... +3 bar; 0 ... 10 V, 3-wire

Pressure transmitter for general applications

Item number:	48717033
Quantity:	1 pcs.
Order code:	S-11-F-BCH-86-Q1ZGM4ZAZ-ZZZ W101Z-ZZ-C3BSZZ-ZFOSE3
Overview:	S-11 ; -1 ... +3 bar; 0 ... 10 V, 3-wire @ 14...30 V DC; Accuracy: 0.5% of span G 1/2 B, flush diaphragm with O-ring Wetted parts: stainless steel Sealing: NBR; circular connector M12x1, 4-pin UB=1, 0V=3, S+=4 Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F) Specifications according to data sheet: PE 81.02
Details:	Pressure transmitter for general applications Model S-11 with flush diaphragm Specifications according to data sheet: PE 81.02 Power supply: DC 10 (14) ... 30 V Case: stainless steel Output signal: 0 ... 10 V, 3-wire Measuring range: -1 ... +3 bar Process connection: G 1/2 B, flush diaphragm with O-ring Wetted parts: stainless steel Sealing: NBR Accuracy: 0.5% of span Electrical connection: circular connector M12x1, 4-pin Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F) Power supply: 14...30 V DC Pin assignment: UB=1, 0V=3, S+=4 shield: standard WIKA standard - specification according to data sheet Test protocol: without test protocol Certificates: without Import documentation CIS-States: without

© 2023 - WIKA Instruments s.a.r.l.