DATASHEET - S811+V42P3S

Soft starter, 420 A, 200 - 600 V AC, Us= 24 V DC, with control unit and pump algorithm, Frame size V

Part no.	**S811+V42P3S**
	168997
EL Number (Norway)	**4137481**

General specifications

Product name	Eaton S811 Soft starter
Part no.	S811+V42P3S
EAN	4015081654918
Product Length/Depth	187.8 millimetre
Product height	420.8 millimetre
Product width	280.6 millimetre
Product weight	41.4 kilogram
Certifications	UL 508 UL File No.: E202571 CSA File No.: LR 353 CCC CSA UL Category Control No.: NMFT CSA22.2-14-1995 CSA-C22.2 No. 14 C-Tick GB14048 UL CSA Class No.: 3211-06 IEC/EN 60947-4-2 CE
Product Tradename	S811
Product Type	Soft starter
Product Sub Type	None
Catalog Notes	Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories Regulator supply: External supply voltage External solution required (reversing contactor)

Features & Functions

Fault memory	10 Faults
Fitted with:	Internal bypass contacts Motor overload protection Display Internal bypass
Functions	Min. ramp time 1 s - fast switching (semiconductor contactor) Single direction Overload monitoring Current limitation Suppression of DC components for motors Underload monitoring Soft start function Potential isolation between power and control sections Suppression of closing transients
Interfaces	Modbus RTU (built-in)

General information

Class	Adjustable
Connection to SmartWire-DT	No
Degree of protection	NEMA Other IP00
Frame size	V
Mains voltage - min	200 V
Mains voltage - max	600 V
Mounting position	As required
Overvoltage category	II
Pollution degree	3
Radio interference class	Class A (EN 55011)
Rated impulse withstand voltage (Uimp)	4000 V

Rated insulation voltage (Ui)	660 V
Shock resistance	15 g, Mechanical
Startup class	CLASS 10 (star-delta replacement) CLASS 30 (6 x I# for 30 s) CLASS 20 (heavy starting duty 3 x I# for 45 s)
Suitable for	Branch circuits, not as BCPD, (UL/CSA)
Type	Soft starter for three-phase loads, with control unit and pump algorithm
Voltage type	DC

Climatic environmental conditions

Altitude	Max. 2000 m Above 2000 m with 0.5 % derating per 100 m
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-50 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30

Main conducting paths

Overload cycle	AC-53a: 4.0 - 32: 99 - 3
Rated operational current (Ie) at AC-53	420 A
Rated operational current (Ie) at AC-53, in-delta	727 A
Rated operational voltage (Ue) - min	200 V
Rated operational voltage (Ue) - max	600 V
Short-circuit protection rating	NZMN3-S500, Type “1” coordination, Main conducting paths
Supply frequency	50/60 Hz, fLN, Main circuit
Voltage rating - max	600 V

Motor rating

Assigned motor power at 200/208 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	350 HP
Assigned motor power at 600 V, 60 Hz, 3-phase	450 HP
Assigned motor power in-delta at 220/230 V, 60 Hz	300 HP
Assigned motor power in-delta at 460/480 V, 60 Hz	600 HP
Assigned motor power in-delta at 575/600 V, 60 Hz	750 HP
Rated operational power at 220/230 V, 50 Hz	132 kW
Rated operational power at 400 V, 50 Hz	200 kW
Rated operational power at 500 V, 50 Hz	250 kW
Rated operational power in-delta at 220/230 V, 50 Hz	200 kW
Rated operational power in-delta at 400 V, 50 Hz	400 kW
Rated operational power in-delta at 500 V, 50 Hz	450 kW

Terminal capacities

Terminal capacity (flexible with ferrule)	4 x (70 - 240) mm^2, Main cables 2 x (120 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables 6 x (120 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables
Terminal capacity (solid)	4 x (70 - 240) mm^2, Main cables 2 x (1 - 2.5) mm^2, Control circuit cables 2 x (120 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables 6 x (120 - 240) mm^2, Main cables
Terminal capacity (solid/stranded AWG)	2 x (14 - 12), Control circuit cables 1 x (14 - 12), Control circuit cables 2 x (4 - 500 kcmil), Main cables 6 x (4 - 500 kcmil), Main cables 4 x (4 - 500 kcmil), Main cables
Terminal capacity (stranded)	2 x (1 - 2.5) mm^2, Control circuit cables 6 x (120 - 240) mm^2, Main cables 4 x (70 - 240) mm^2, Main cables 1 x (2.5 - 4) mm^2, Control circuit cables 2 x (120 - 240) mm^2, Main cables
Screwdriver size	0.6 x 3.5 mm, Terminal screws, Control circuit cables
Tightening torque	0.4 Nm, Screw terminals, Control circuit cables

Control circuit

Current consumption	100 mA, Control circuit, Digital inputs, External 24 V (no-load) 1400 mA, Control circuit, Regulator supply 150 mA, Control circuit, Digital inputs, External 24 V 10 A/150 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC
Drop-out time	100 ms, DC operated
Drop-out voltage	0 - 3 V, DC operated
Pick-up time	100 ms at DC
Pick-up voltage	21.6 - 26.4 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	24 V

Input/Output

Input current	4 - 20 mA (Analog inputs)
Number of inputs	1 (current input)
Number of outputs	2 Relay Outputs (programmable)
Output voltage	120 V AC/DC (relay outputs)
Protection	Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)	24 V DC (-10 %/+10 %) 24 V DC
Rated operational current (Ie) at AC-11	3 A

Soft start function

Application	Soft starting of three-phase asynchronous motors 3-phase motors: Yes
Delay time	0 - 120 s, Soft start function, Ramp times
Kickstart	Max. 2000 ms (Kickstart Duration) 100% (Kickstart voltage)
Ramp/run-up time	360 s
Start voltage	Max. 85 %, Soft start function, Start voltage = turn-off voltage

Design verification

Equipment heat dissipation, current-dependent Pvid	25 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	420 A
Static heat dissipation, non-current-dependent Pvs	25 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecl@ss13-27-37-09-07 [ACO300016])

Rated operation current Ie at 40 °C Tu		A	420
Rated operating voltage Ue		V	200 - 600
Rated power three-phase motor, inline, at 230 V		kW	132
Rated power three-phase motor, inline, at 400 V		kW	200
Rated power three-phase motor, inside delta, at 230 V		kW	200
Rated power three-phase motor, inside delta, at 400 V		kW	400
Function			Single direction
Internal bypass			Yes
With display			Yes
Torque control			No
Rated surrounding temperature without derating		°C	50
Rated control supply voltage AC 50 Hz		V	0 - 0
Rated control supply voltage AC 60 Hz		V	0 - 0
Rated control supply voltage DC		V	24 - 24
Voltage type for actuating			DC
Integrated motor overload protection			Yes
Release class			Adjustable
Degree of protection (IP)			IP00
Degree of protection (NEMA)			Other

© 04/2023 by Eaton Industries GmbH