Product data sheet
Characteristics

ZCKD219
limit switch head ZCKD - thermoplastic roller lever plunger with protective boot



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKL XCKM
Associated body	ZCKMD31H29 ZCKMD35H7 ZCKLD37H7 ZCKMD39H7 ZCKM6H7 ZCKMD31 ZCKMD39H29 ZCKL8 ZCKM6H29 ZCKM8 ZCKLD37 ZCKL1H7 ZCKMD31H7 ZCKM8H29 ZCKL5 ZCKL1 ZCKMD35 ZCKM1 ZCKL7 ZCKM5H7 ZCKM5 ZCKL7H7 ZCKLD35H7 ZCKLD35 ZCKL5H7 ZCKM9H29 ZCKM8H7 ZCKM7H7 ZCKM6 ZCKL6

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	ZCKMD35H29 ZCKM9 ZCKM1H29 ZCKL8H7 ZCKMD39 ZCKMD37H29 ZCKM7H29 ZCKL6H7 ZCKM7 ZCKMD37H7 ZCKM5H29 ZCKLD39 ZCKMD37 ZCKLD31H7 ZCKLD39H7 ZCKLD31 ZCKM1H7
Movement of operating head	Rotary Linear
Type of operator	Roller lever plunger spring return thermoplastic (with protective boot)
Type of approach	Lateral approach 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1037 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months