Date: 11/04/2023

PSD-4-ECO ; 0...10 bar gauge; two switching outputs (PNP)

PSD-4-ECO ; 0...10 bar gauge; two switching outputs (PNP)

Item number:	48792136
Quantity:	1 pcs.
Order code:	PSD-4-ECO-D-BG410-1GI1-2O2DIZS-ULZZ-W1011P4E-ZZOSW-GSFJ
Overview:	PSD-4-ECO ; 0...10 bar gauge; two switching outputs (PNP) OEM Pressure Switch with Display Output signal: two switching outputs (PNP) IO-Link: IO-Link 1.1 Power supply: 15 ... 32 V DC Measuring range: 0...10 bar gauge Process connection: G1/4 A ISO1179-2 Sealing: NBR Permissible medium temperature: -25...+85°C Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1,SP2=2, U-=3, SP1 =4 Overload Safety: 2 x Accuracy: 1.0% of span Approvals: cULus Type of packaging: single packaging Specifications according to data sheet: PE 81.69
Details:	PSD-4-ECO ; 0...10 bar gauge; two switching outputs (PNP) OEM Pressure Switch with Display Output signal: two switching outputs (PNP) IO-Link: IO-Link 1.1 Power supply: 15 ... 32 V DC Measuring range: 0...10 bar gauge Process connection: G1/4 A ISO1179-2 Sealing: NBR Permissible medium temperature: -25...+85°C Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1,SP2=2, U-=3, SP1 =4 Overload Safety: 2 x Accuracy: 1.0% of span Approvals: cULus Type of packaging: single packaging Specifications according to data sheet: PE 81.69

© 2023 - WIKA Instruments s.a.r.l.