Specifications

Eaton CH223DIU



Catalog Number: CH223DIU

Eaton Bussmann series 3-Pole modular fuse holder, rated at 690 V a.c./1000 V d.c. (IEC), 700 V a.c. (UL) , 125 Amps (IEC), 100 A (UL), fitted with a neon indicator, suitable for 22 x 58 mm Cylindrical fuses

General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse holder

Catalog Number
CH223DIU

EAN
5027590497114

UPC
051712685405

Product Length/Depth
77 mm

Product Height
123 mm

Product Width
107 mm

Product Weight
559.5 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269-2
EAC
IEC 60269-1
UL Listed File E14853

Powering Business Worldwide

Product specifications

Used with

C22G, C22M, FWP-(amps)A22F fuses

Type

fuse accessory

Application

Industrial and Commercial applications

Amperage Rating

125 A

Number of Poles

Three-pole

Width in number of modular spacings

6

Built-in depth

51.5 mm

Fitted with:

Neon indicator

Fuse size

22 x 58 mm

Operating temperature details

-20ºC to +70ºC

Voltage rating at AC

690 V a.c. (IEC) and 700 V a.c. (UL)

Voltage rating at DC

1000 V d.c. (IEC)

Fuse type

C22G

C22M

Lockable

Yes

Accessories

JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory, CH22-TPS Microswitch to work with CH223D(I)U

Torque rating

Min 4 Nm/ Max 5 Nm

Concurrently switching N-neutral

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA Modular fuse-holders

CE Modular fuse-holders

Multimedia

Eaton Bussmann – Modular fuse holders

Technical data sheets

720147 10 x 38 mm Modular fuse holder

10080 14 x 51 mm Modular fuse holder

10115 22 x 58 mm Modular fuse holder

No

Material

Polyester

Optical defect indication

Yes

Mounting method

DIN rail

2 x M4 Panel mounting screws

Degree of protection

IP20

Voltage rating

690 V

Model

CH22

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia