LPSSL1206

Illuminated selector switch actuator Ø22mm Platinum series metal, 2 position, 0 - 1. Blue



Product designation			Illuminated selector switch actuator - 2 position
Product type designation			LPSSL12
General characteristics			
Colour			Blue
Type of positions			0 - 1
Material			Aluminium and zinc alloy
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Mechanical life		cycles	1000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-25
	max	°C	+70
	Storage temperature		
	min	°C	-40
	max	°C	+85

Dimensions



Certifications and compliance	
Compliance	
	CSA C22.2 n° 14
	IEC/EN/BS 60947-1
	IEC/EN/BS 60947-5-1
	UL508
Certificates	
	cULus
	RINA
ETIM classification	

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

ETIM 8.0

EC002611 -
Control switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding