PREVO S1 Safety quick release couplings one push - ESI 11

Parallel male thread coupler



Technical characteristics

- **Profile:** European 10,4 mm
- **Technology:** "One push" safety system (avoids hose whip)
- **Operating pressure:** 2 to 16 bar
- **Flow rate at 6 bar:** 3530 l/min (ΔP = 0,6 bar)
- **ID Passage:** 10,4 mm
- **Temperature:** -15°C to +70°C
- **Construction:** Body : Stainless steel
- **Highlight:** Anti-static, Excellent efficiency, Harsh conditions



A (mm)	B (mm)	C (mm)	BSPP male thread	Parts Numbers
100,4	37	26	G 3/8	**ESI 111152**
101,4	37	26	G 1/2	**ESI 111153**
105,9	37	32	G 3/4	**ESI 111154**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.