Date: 22/04/2024

F2808 50 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression

Miniature Tension-/Compression force transducer S-Type

Item number: 83800525

Quantity: 1 pcs.

Order code: SPP-F2808-M2150C3A4K010300XXXXXXXXXXXXXXXXXXXX
M1066FO5168

Overview: F2808 50 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression

Model: F2808 Tension/compression force transducer, S-Typ, female thread
Force direction: tension/compression
Rated force/Rated load: 50 N
Relative linearity error: ±0.15% Fnom
Output signal: 2.0 ±0.2 mV/V
Electrical connection: Cable output, free wires
Cable length: 3 m
Force transmission: M4
Ingress Protection IP: IP66
Technical data acc. to datasheet: FO51.68

Details: Miniature Tension-/Compression force transducer S-Type
Model: F2808 Miniature S-Type up to 2,000 N
Force direction: tension/compression
Unit: N
Nominal load: 50 N
Output signal: 2 mV/V, 4-wire
Electrical connection: cable outlet, length 3m
Cable length in m: 3,0m
Data sheet: FO 51.68
Product Name: Tension/compr. force transd. Mini. S-Typ
SPP-Tension-/compression force transducer, model F2808
Technical data acc. to datasheet: FO51.68
Model: F2808 Tension-/compr. force transd., S-Type Miniature,female thread, 0..5N-0..2,000N
Force direction: tension/compression
Rated force/Rated load: 50 N
Relative linearity error: ±0.15% Fnom
Output signal: 2.0 ±0.2 mV/V
Electrical connection: Cable output, free wires
Cable length: 3 m
Force transmission: M4
Ingress Protection IP: IP66
Miniature Tension-/Compression force transducer S-Type
Model: F2808 Miniature S-Type up to 2,000 N
Force direction: tension/compression

© 2024 - WIKA Instruments s.a.r.l.

Unit: N
Nominal load: 50 N
Output signal: 2 mV/V, 4-wire
Electrical connection: cable outlet, length 3m
Cable length in m: 3,0m
Data sheet: FO 51.68
Product Name: Tension/compr. force transd. Mini. S-Typ

© 2024 - WIKA Instruments s.a.r.l.