TEGERA®



TEGERA® 52

Leather glove, unlined, 0,7-0,8 mm split cowhide, cotton, Cat. II, grey, white, elasticated 180°, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, durable, good fit

SPECIFICATION

TYPE OF GLOVE **Work gloves - General handling**

CATEGORY **Cat. II**

SIZE RANGE (EU) **7, 8, 9, 10, 11**

PALM MATERIAL **Split cowhide**

PALM THICKNESS **0,7-0,8 mm**

BACK MATERIAL **Cotton**

LINING **Unlined**

DEXTERITY **4**

FASTENING **Elasticated 180°**

LENGTH RANGE **220-250 mm**

COLOUR **Grey, white**

PAIRS PER PACKAGE/CARTON **12/120**

PIECES PER BOX **12**

DISPLAY **Thread**

MATERIAL SPECIFICATION **Leather, cotton, natural latex**

SIZE	ART. NO.	EAN NO.
8	52-8	7392626003255
10	52-10	7392626003262
7	52-7	7392626008298
9	52-9	7392626008304
11	52-11	7392626017207

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 52

PREVENTS RISK OF
Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE
Dry environments, dirty environments

PRIMARY AREAS OF USE
Assembly, machine operating, repair work

PRIMARY INDUSTRIES OF USE
Automotive, transportation, utilities, building and construction, logistics

TYPE OF WORK
Medium weight

CE Cat. II

EN 420:2003
+ A1:2009

EN 388:2016
3032X

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

TEGERA®

TEGERA® 52



CE Cat. II

EN 420:2003 + A1:2009 EN 388:2016 3032X

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing
(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ⩽ 9 kN)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com