DATASHEET - IZMX-TF403-1600W-1

Connections, front, 1600A, IZMX40, 3 p, withdrawable

Part no.	**IZMX-TF403-1600W-1**
	184177
EL Number (Norway)	**4398520**

General specifications

Product name	Eaton Moeller series IZMX/INX main terminal
Part no.	IZMX-TF403-1600W-1
EAN	4015081783496
Product Length/Depth	400 millimetre
Product height	200 millimetre
Product width	400 millimetre
Product weight	12.6 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Main terminal

Delivery program

Type	Accessory
Amperage Rating	800 A - 1600 A
Special features	Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard. This connection kit comes with front terminals for connection to the cassette. The circuit breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit breaker is installed in the enclosure. This way, the final connection to the circuit breaker can be made from the front.
Suitable for	Three-pole
Used with	INX40…3…08W Three-pole IZMX40…3…12W INX40…3…10W INX40…3…12W INX40…3…16W IZMX40…3…08W IZMX40…3…16W IZMX40…3…10W

Technical Data - Mechanical

Mounting Method	Withdrawable

Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Additional information

Accessory/spare part type	Main terminal kits

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss13-27-37-13-05 [ACN990017])

Suitable for number of poles	3

© 04/2023 by Eaton Industries GmbH