

Note :

Source Resolution UXGA:
7680x4320 @60Hz
3840x2160 @120HZ

Specification :

1.	Cabe	UL20276, (1P(32AWG)+AL/MY)*5 + 3C(32AWG) + 1C(28AWG) + 2C(24AWG) + AL+BD, Jacket Color: Black, OD: 4.6±0.15 mm
2.	Conn.	USB Type C Plug, Conductor: Gold Plated, Shell: Nickel Plated
3.	Conn.	DisplayPort Plug, Conductor: Gold Plated, Shell: Nickel Plated
4.	Hood	For USB Type C Plug, ABS, Color: Black
5.	Hood	For DisplayPort Plug, ABS, Color: Black
6.	Inner molding	LDPE
7.	S.R.	Black PVC: 45P

Part No.	Length	Resistance
11.04.5835	1000 mm	2 ohm
11.04.5836	2000 mm	2 ohm
11.04.5837	3000 mm	2 ohm

SECOMP

Issue Date : 2020/11/05

Product Name	ROLINE Adaptercable USB Type C-DP, v1.4(8K60Hz), M/M
Product No.	11.04.5835/11.04.5836/11.04.5837

Approve	Check	Draw	Design
Allen	Allen	Kuan	Kuan

Scale 1:1 | Unit : mm

Rev.	Date	Contents of Change	Design
1			
2			
3			