Specifications

Eaton 102422



Catalog Number: 102422

Eaton xEnergy Basic LV systems Low voltage switchgear. Metal door, for HxW=2060x600mm

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102422
EAN	**Product Length/Depth**
4015081023103	45 mm
Product Height	**Product Width**
2010 mm	615 mm
Product Weight	**Compliances**
10.6 kg	RoHS conform

Powering Business Worldwide

Product specifications

Special features

Can be used as left door for two-leaf versions
Closed
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Left door for two-section design with 1200 mm enclosure widths

Type

Additional equipment for floor-standing service distribution board
IVS

Features

EMC-version

Accessory/spare part type

Doors

Surface finishing

Powder coating
With powder coating

Color

Light gray (RAL 7035)
Gray

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

2060 mm

Suitable for width

600 mm

Cover/door type

Three-point turn-lock

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_Z-DS

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Material

Sheet steel

Steel

Housing material

Sheet steel

Model

Stop door

Mounting method

Floor standing distribution board

Flush mounting

Surface mounting

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia