# REBEL™ SELF RETRACTING LIFELINE (SRL)




# TOTAL COMPLIANCE. ABSOLUTE CONFIDENCE.

PROTECTA

TRUSTED, QUALITY FALL PROTECTION OVER 50 YEARS

PRODUCT SHEET

2011

# DEPENDABILITY
## YOU CAN RELY ON EVERY DAY

## Protecta® continues to set the standard for performance and value.

The Rebel™ SRL line is built to last providing an economical fall protection solution without compromising performance or safety!




## Durable

- Built to last
- Heavy-duty housing types
  - Aluminium
  - Thermoplastic
- Stackable

## Markets Served

- Commercial Construction
- Residential Construction
- Industry & Manufacturing
- Roofing
- Steel erection

And more !

## Reliable

- 140 kg capacity
- Side cable exit
- Double swivel
- Fall indicator hook

## Easy to maintain

- The design of the SRL is made up of 30% parts less than usual SRL
- Several parts are common to different model sizes
- It makes the maintenance to be quicker and easier when the block needs to be maintained

## Easy to inspect

- Internal design and fall indicator hook allow a competent person to visually perform the yearly inspection
- No need to send the SRL back to authorized service centers for yearly inspection

## Sharp edge compliant

- Meets the last updated CE sharp edge certification for horizontal use

# EXPLORE THE SYSTEM

**140 kg Capacity**

High capacity for operator and tools

**Top Swivel**

Limits lifeline twisting

**Stackable**

Housing design allows for stacking on work surfaces

**Thermoplastic Housing**

Lightweight, compact and durable

or

**Aluminium Housing**

Provides exceptional strength and durability




**Ergonomic Carrying Handle**

Built-in design makes transport, set-up and storage easy

**Side Cable Exit**

Enables smooth operation and reduces cable wear

**Use of additional sling extension**

Ref : 3500050 allows all Rebel to be used on horizontal and to meet CE sharp edge certification

**Ergonomic Cable Handle**

Provides added comfort and ease-of-use when making connections

**Galvanized and SS Cable**

Stainless steel option for added corrosion resistance

**Swivel Hook**

Limits lifeline twisting

**Unique Packaging**



**Impact Indicator**

Provides visual indication of Fall Arrest

**Self Locking Snap Hook**

Automatically closes and locks for added safety

**1,633 kg Gate Capacity**

Reduces chance of accidental disengagement (“roll-out”)

# REBEL™ SELECTION TABLE

| Reference | Length (m) | Depth (cm) | Width (cm) | Height (cm) | Weight (kg) | Housing type | Cable material |
|---|---|---|---|---|---|---|---|
| 3590520 | 6 | 12 | 25 | 57 | 5,3 | Plastic | Galvanised |
| 3590530 | 6 | 12 | 25 | 57 | 6,7 | Aluminium | Galvanised |
| 3590521 | 10 | 12 | 25 | 57 | 5,6 | Plastic | Galvanised |
| 3590531 | 10 | 12 | 25 | 57 | 7,0 | Aluminium | Galvanised |
| 3590522 | 10 | 12 | 25 | 57 | 5,6 | Plastic | Stainless Steel |
| 3590532 | 10 | 12 | 25 | 57 | 7,0 | Aluminium | Stainless Steel |
| 3590570 | 15 | 12 | 28 | 61 | 7,5 | Plastic | Galvanised |
| 3590580 | 15 | 12 | 28 | 61 | 9,1 | Aluminium | Galvanised |
| 3590571 | 15 | 12 | 28 | 61 | 7,5 | Plastic | Stainless Steel |
| 3590581 | 15 | 12 | 28 | 61 | 9,1 | Aluminium | Stainless Steel |
| 3590610 | 20 | 14 | 33 | 65 | 10,0 | Plastic | Galvanised |
| 3590620 | 20 | 14 | 33 | 65 | 12,4 | Aluminium | Galvanised |
| 3590611 | 20 | 14 | 33 | 65 | 10,0 | Plastic | Stainless Steel |
| 3590621 | 20 | 14 | 33 | 65 | 12,4 | Aluminium | Stainless Steel |
| 3590650 | 25 | 14 | 33 | 65 | 13,0 | Plastic | Galvanised |
| 3590660 | 25 | 14 | 33 | 65 | 15,4 | Aluminium | Galvanised |
| 3590651 | 25 | 14 | 33 | 65 | 13,0 | Plastic | Stainless Steel |
| 3590661 | 25 | 14 | 33 | 65 | 15,4 | Aluminium | Stainless Steel |
| 3590690 | 30 | 14 | 33 | 65 | 13,4 | Plastic | Galvanised |
| 3590700 | 30 | 14 | 33 | 65 | 15,8 | Aluminium | Galvanised |
| 3590691 | 30 | 14 | 33 | 65 | 13,4 | Plastic | Stainless Steel |
| 3590701 | 30 | 14 | 33 | 65 | 15,8 | Aluminium | Stainless Steel |

**A specific range of the Rebel™ SRL** also exist with shorter length :

Web lifeline: Robust aluminium housing for length of 3m (ref.: AD111) to 6m (Ref.: AD120)

Lightweigth plastic housing for a 6m length (ref.: 3101041)

Cable Lifeline: Robust aluminium housing for a 4,5m length




©2011, Capital Safety

capital SAFETY

Capital Safety Group - Europa, Middle-East, Africa
Le Broc Center Z.I. 1re Avenue 5600 m B.P. 15
06511 Carros Le Broc Cedex - France
Tel : + 33 (0)4 97 10 21 11
Fax: + 33 (0)4 93 08 79 70
information@capitalsafety.com
www.capitalsafety.com

Capital Safety Group - Northern Europe
7, Christleton Court - Stuart Road - Manor Park
Runcorn Cheshire - WA7 1ST - UK
Tel : + 44 (0) 1928 571324
Fax: + 44 (0) 1928 571325
csgne@capitalsafety.com
www.capitalsafety.com