

# MULTIMASTER MM 700 1.7 Q Grouting Renewal

## Oscillating multi-tool – MM 700

Our best MultiTool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Product number: 7 229 70 66 00 0

## Details

- Precision – MultiTools get into hard-to-reach places. Thanks to vibration damping, they work quietly and precisely.
- Versatility – blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- Safety and simplicity – MultiTools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- 12-sided holder for optimum torque transfer.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

## Price includes

- 5 Cutter blades, straight (form 117) 6 390 31 17 01 5
- 1 Cutter blade, mushroom shaped 6 390 31 28 01 2
- 1 protective cover for tool changes
- 1 plastic tool case (L-BOXX 238)
- 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1
- 1 handle
- 1 sharpening stone (63719010014)

## Technical data

### TECHNICAL DATA

| | |
|---|---|
| Input | 450 W |
| Output | 250 W |
| Oscillations | 10,000 - 19,500 rpm |
| Tool Holder | 12-sided |
| Tool change | QuickIN |
| Amplitude | 2 x 1,7° |
| Cable with plug | 5 m |
| Weight according to EPTA | 1.65 kg |
| Weight according to EPTA | 1.65 kg |

## VIBRATION AND SOUND EMISSION VALUES

| | |
|---|---|
| Sound pressure level LpA<br>Uncertainty of measured value KpA | 82 dB<br>3 dB |
| Sound power level LWA<br>Uncertainty of measured value KWA | 93 dB<br>3 dB |
| Sound peak value LpCpeak<br>Uncertainty of measured value KpCpeak | 96 dB<br>3 dB |
| Uncertainty of measured value Kα | 1,5 m/s² |

## Application examples

