PRODUCT-DETAILS

OT60FT3

OT60FT3 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT60FT3
Product ID	1SCA105081R1001
EAN	6417019392110
Catalog Description	OT60FT3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, door mounted, switch-diconnector / non-fusible diconnect switch with front protected clamp terminals, handle and shaft are not included

ABB EcoSolutions

Environmental Product Declaration - EPD	1SCC301280D0201

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201

© 2025 ABB. All rights reserved.

RoHS Declaration	1SCC011020D0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301060M0004
Mechanical Drawings	1SCC301470F0001 1SCC301469F0001 OT125FT3.igs
Environmental Product Declaration - EPD	1SCC301280D0201

Environmental

Degree of Protection	Front IP20
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country or Territory of Origin	Finland

Dimensions

Product Net Width	70 mm
Product Net Height	100 mm
Product Net Depth / Length	66.5 mm
Product Net Weight	0.42 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	71 mm
Package Level 1 Height	76 mm
Package Level 1 Gross Weight	0.44 kg
Package Level 1 EAN	6417019392110

Technical

Cable Cross-Section	Cu 2.5 ... 25 mm²
Connecting Capacity Main Circuit	Flexible 1x Cu 2.5…25 mm² Stranded 1x Cu 2.5…25 mm²

© 2025 ABB. All rights reserved.

Degree of Protection	Front IP20
Handle Type	Handle and shaft not included
Mechanical Durability	20000
Mounting Type	Door mounting
Number of Poles	3P
Operating Mode	Front
Pollution Degree	3
Power Loss	at Rated Operating Conditions per Pole 1.6 W
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 40 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 37 kW (500 V) 37 kW (690 V) 37 kW
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 3.6 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 2.5 kA
Recommended Screw Driver	Main Circuit Hexagon 4
Special Functions	No
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 6.2 N·m
Wire Stripping Length	Main Circuit 17-18 mm

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	60 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 3 Hp (240 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 20 Hp (440 ... 480 V AC) Three Phase 40 Hp (550 ... 600 V AC) Three Phase 40 Hp
Wire Stripping Length	Main Circuit 17-18 mm
Recommended Screw Driver	Main Circuit Hexagon 4
Tightening Torque	acc. IEC 60947-1 6.2 N·m

Certificates and Declarations

A2L Certificate – IEC	1SCC301335D0201
ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301010D0201

© 2025 ABB. All rights reserved.

UL Certificate	cULus certificate OT30-125
VDE Certificate	No certification needed

External Classifications and Standards

Object Classification Code	Q
ETIM 9	EC000216 - Switch disconnector (low voltage)
ETIM 10	EC000216 - Switch disconnector (AC)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors



© 2025 ABB. All rights reserved.