Shower Fan Kits



Description

Shower fan kits include all parts necessary to complete the installation. The light version includes an option of either white or chrome bezels

Features

- Low energy fans – meet Building Regulation L1A specific fan power of less than 0.5W/l/s
- Low noise fans – meet Building Regulation F1 by being under 35dB for less noise sensitive rooms
- Over run timers factory set at 15 minutes
- Includes 3 metres of flexible ducting
- Round grille for fitting above shower, square grille for use outside
- Fans have a one shot thermal fuse
- 3-year guarantee

Range

4” (100mm) Shower Fan Kit – Timer	4640
4” (100mm) Shower Fan Kit – Light and Timer	4641

Technical Specification

	Light Shower Fan	Shower Fan
Extraction rate	30 l/s (107m³/hr)	30 l/s (107m³/hr)
Specific Fan Power	0.47W (l/s)	0.47W (l/s)
Noise level	28dB @ 3m	28dB @ 3m
Voltage	240Vac	240Vac
Motor Rating	14W	14W
IP Rating	IP X4	IP X4
Ambient Temp	40°C Max.	40°C Max.
Insulation Class	Double Insulated	Double Insulated
Over Run Timer	2-30 mins.	2-30 mins.
Lamp	20W 12V	

No user serviceable parts

Standards

- BS EN 60335-2-80

Deta Electrical Company Ltd.
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk