Specifications

Eaton 183044



Catalog Number: 183044

Eaton xEffect - XNH circuit protection. NH fuse-switch 3p box terminal 35 - 150 mm², mounting plate, NH1

General specifications

Product Name	**Catalog Number**
Eaton xEffect XNH device for mounting plate	183044
	EAN
	4015081779710
Product Length/Depth	**Product Height**
306 mm	117 mm
Product Width	**Product Weight**
184 mm	2.031 kg
Compliances	**Certifications**
RoHS conform	IEC/EN 60947-3

Powering Business Worldwide

Product specifications

Type

Basic device

Special features

Current paths of electrolytic copper, silver-plated
Permanent operation (rated operating mode)

Features

Halogen free
Standard sealable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Brochures

eaton-xeffect-xnh-fuse-switch-disconnector-brochure-br019002en-en-us.pdf

Catalogs

eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf

Certification reports

eaton-xeffect-xnh-fuse-switch-disconnector-declaration-of-conformity-en-us.pdf

Drawings

eaton-circuit-breaker-xeffect-xeffect-xnh-circuit-protection-dimensions-003.eps

eCAD model

ETN.XNH1-A250-BT.edz

Installation instructions

IL0131110ZU

mCAD model

eaton-XNH1-A250-drawing.dwg

eaton-XNH1-A250-3d-model.stp

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Ui = 800 V AC

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frequency rating

40 Hz - 60 Hz

Pollution degree

3

Creepage resistance

CTI 600

Equipment heat dissipation, current-dependent

16 W

Rated uninterrupted current (Iu)

250 A

Total heat dissipation without fuses at ith

16 W

Ambient operating temperature details

Ambient temperature range: -25 °C - 55 °C

Voltage rating at AC

400 V (AC-23B)
500 V (AC-22B)
690 V (AC-21B)

Voltage rating at DC

250 V (DC-22B)
440 V (DC-21B)

Conditioned rated short-circuit current Iq

120 kA

Number of poles

Three-pole

Rated operation power at AC-23, 400 V

0 kW

Size

NH1 fuse

Rated impulse withstand voltage (Uimp)

8 kV

Color

Gray

Connection type

Box terminal

Degree of protection

IP10 (handle cover open, XNH installed)
IP20 (operating status, XNH installed)
IP2XC (contact protection, XNH installed)

Rated short-time withstand current (Icw)

6 kA

Direction of incoming supply

As required

Electrical connection type of main circuit

Frame clamp

Activation type

Dependent manual activation

Actuator position

Front side

Actuator type

Cover grip

Voltage test

Yes, sliding inspection windows

Heat dissipation at 80% without fuses

10.2 W

Heat dissipation per pole, current-dependent

5.3 W

Mounting position

Vertical or horizontal

Suitable for

Ground mounting

Rated conditional short-circuit current (Iq)

120 kA

Overvoltage category

III

Suitable for fuses

NH1

Material

Polyamide

Cable entry type

Other

Frequency rating of contacts

40 Hz - 60 Hz

Mounting method

DIN rail

Mounting plate

Rated operation current (Ie)

250 A

Locking facility

Yes, optional

Flammability characteristics (UL)

Self-extinguishing (UL 94)

Degree of protection (front side)

Other

Heat deflection temperature

125 °C

Lifespan, electrical

200 operations

Lifespan, mechanical

1400 operations

Terminal capacity (copper busbar)

30 mm x 10 mm

Max. 37 mm cable lug width at flange connection

Bolt diameter at flange connection: M10

Terminal capacity (copper band)

6 mm x 16 mm x 0.8 mm (6x) at box terminal

Terminal capacity (stranded cable)

25 mm² - 150 mm² at box terminal

10 mm² -150 mm² at clamp-type terminal

35 mm² - 150 mm² at box terminal

70 mm² - 95 mm² (2x) at double clamp-type terminal

Rated operational current

250 A (AC-22B)

250 A (AC-21B)

250 A (DC-21B)

250 A (DC-22B)

250 A (AC-23B)

Operating altitude without derating - max

2000 mm

Permitted power loss per fuse link - max

23 W

Power rating at AC-23, 400 V

0 kW

Rated insulation voltage (Ui)

800 VAC

Rated operating voltage (Ue) at AC - max

690 V

Rated operational current for specified heat dissipation (In)

250 A

Rated conditional short-circuit rating

100 kA (690 V)

120 kA (500 V)

Terminal capacity (copper strip)

16 mm x 0.8 mm (10x) at box terminal



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia