EXHAUST FILTER, IP54

CATALOG NUMBER

EFA200R5



This vertical exhaust filter, EFA, with a IP 54 protection degree, is easy to install thanks to its click-in feature. Unnecessary downtime is avoided, since water and dust are prevented from entering the enclosure through the filter.

INDUSTRY STANDARDS

cRUus_UL

CE UKCA

EAC

FEATURES

Description: Exhaust filter to be used for natural ventilation, or for forced ventilation working with filter fans EF. nVent HOFFMAN exhaust filters save us time because are installed with a click-in system without screws. The hinged front cover can be easily opened for quick and easy filter replacement.

Material: Front cover made of injection-moulded thermoplastic, self-extinguishing, UL94V0.

Temperature range: -40 °C to +55 °C.

Protection: IP 54, TYPE 12.

Finish: RAL 7035.

Approvals: CE, EAC, cRUus_UL Recognized.

Pack quantity: One exhaust filter.

Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the enclosure

The click-in feature reduces the customer's labour cost due to the ease of installation

To guarantee natural ventilation, install at least two exhaust filters

Forced ventilation can be achieved by adding filter fans, EF

Filter mat (EN779): EFA100R5, EFA200R5, EFA220R5, EFA250-300R5 - G4; EFA500-700R5 - G3

Filtration efficiency (%): >90

PRODUCT ATTRIBUTES

Height: 145 mm

Width: 145 mm

Depth: 26 mm

Product Family: Climate Control
Material: Thermoplastic
Finish: Smooth
Color: Light Gray
Color Code: RAL 7035
Weight: 0.2 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.