Professional Rubber Power Distributor BSV 5 2 m H07RN-F 5G6,0 1xCEE32 A+2x16 A, 6x230 V

Leichter und mobiler Stromverteiler für den Einsatz im Außenbereich, IP 44.









MADE IN GERMANY | 5 YEARS MANUFACTURER GUARANTEE | IP 44

Product number	9150320061
EAN	4007123687909

DESCRIPTION

- Ergonomically shaped carrying handle with recessed grip for easy transport even with thick work gloves.
- High and non-slip rubber feet against floor-related dirt.
- Fuse elements (FI and LS switch) in the distributor interior.
- Highest operational safety by connecting each individual 230 V earthing contact socket to an LS switch.
- Extremely robust, impact resistant, resistant to ageing and weathering.
- Resistant to various oils, greases, petrol and acids, UV and ozone radiation.
- Self-closing lid with quick release fastener and robust hinges.
- Oil resistant rubber cable for continuous outdoor use.
- Quality sockets according to VDE 0620-2-1.
- CEE sockets with nickel-plated contacts.
- Connected load from 11 to 22 kVA.
- With residual current circuit breaker.
- Operation of several loads at a three-phase / heavy current connection point with plug systems to IEC 60309.
- Belt for cable fixation.

Professional Rubber Power Distributor BSV 5 2 m H07RN-F 5G6,0 1xCEE32 A+2x16 A, 6x230 V

Leichter und mobiler Stromverteiler für den Einsatz im Außenbereich, IP 44.



Product number	9150320061
EAN	4007123687909

TECHNICAL DATA

Cable quality	Rubber-Neoprene	**Number of poles (FI)**	4
Cable length	2 m	**CEE 400 V / 16 A / 3P+N+PE (5p) Steckdosen**	2
Cable designation	H07RN-F 5G6,0	**CEE 400 V / 32 A / 3P+N+PE (5p) Steckdosen**	1
Cable colour	black	**Earthed socket outlets**	6
Max. current carrying capacity	32 A	**Plug system socket**	Type F (Protective contact)
Miniature circuit breaker	8	**Supply/ connection option**	Supply cable with plug
Residual current circuit breaker (RCCB)	FI with IFN 0.03 A (standard)	**Plug system plug**	CEE 32 A 3P+N+E (5p) 400 V
Rated current (FI)	30 mA	**Degree of protection (IP)**	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

Packaging	Neutral carton	**Dimension LxWxH (without packing)**	31 cm x 53 cm x 30 cm
UP	1	**Weight of product (including packaging)**	7.71 kg
Weight of product (without packaging)	7.71 kg	**Dimension LxWxH (incl. packing)**	53 cm x 31 cm x 30 cm

SCOPE OF DELIVERY

Professional Rubber current distributor BSV 5, fixing strap