Date: 21/04/2023

PGS43.100...LM-D50 400 mbar G1/2B

switchGAUGE PGS43.100/160

Item number:	58414707
Quantity:	1 pcs.
Order code:	PGS43.100.23ZZZPZ-MG240Z-AGD-IZ-LM-D50-ZZZIZ-ZZZZ5TZZZ 33DZHJFSGZZZ-ZZZZZZ11Z
Overview:	PGS43.100...LM-D50 400 mbar G1/2B magnetic snap action switch, model 821.3 plug sidewise Connection location: lower mount Case: with pressure blowout disk class 1.6 Diaphragm Material: Inconel 718 (2.4668) Sealing of pressure chamber: FPM Process connection: G 1/2 B Overpressure safety: 5 x Full scale value, max 40 bar Window: laminated safety glass Ingress protection: IP 54 Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Permissible ambient temperature: -20 … +60 °C Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number *...*
Details:	switchGAUGE PGS43.100/160 pressure gauge with switches, diaphragm measuring system Specifications according to data sheet: PV 24.03 and AC 08.01 switch: magnetic snap action switch, model 821 first switch operation: change over (3) Electrical connection: plug sidewise Nominal size: 100 Scale range: 0...400 mbar Overpressure safety: 5 x Full scale value, max 40 bar Diaphragm Material: Inconel 718 (2.4668) Lower Body Material: Stainless-Steel Connection location: lower mount Liquid Damping (case filling): without filling Case: with pressure blowout disk Pressure Gauge Standard: International (standard Europe) Accuracy class: class 1.6 Case material: Stainless steel 1.4301 Case surface: bare Window: laminated safety glass Sealing of pressure chamber: FPM

© 2023 - WIKA Instruments s.a.r.l.

Ingress protection: IP 54
Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F)
Permissible ambient temperature: -20 … +60 °C
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*
Process connection: G 1/2 B

© 2023 - WIKA Instruments s.a.r.l.