LPSBL7223

Double-touch actuator, spring return, white indicator Ø22mm Platinum series metal, 1 extended and 1 flush pushbuttons. Both spring return, Green - Red/I - 0



Product designation	Double-touch actuators, spring return white indicator - One extended and one flush pushbuttons
Product type designation	LPSBL72

General characteristics

Colour	Green/Red
Type of positions	I - O
Material	Aluminium and zinc alloy for metal parts and polyamide for plastic parts
IEC degree of protection	IP66, IP67 and IP69K

Mechanical features

Fixing	Without mounting adapter
Mounting adapter	LPXAU120M

UL technical data

UL degree of protection	Type1, 2, 3R, 4, 4X, 12, 12K

Ambient conditions

Temperature

Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LPSBL7223

Double-touch actuator, spring return, white indicator Ø22mm Platinum series metal, 1 extended and 1 flush pushbuttons. Both spring return, Green - Red/I - 0

Certificates

cULus	
RINA	

ETIM classification

ETIM 8.0	EC000029 - Push-switch button

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding