CAT. N° 0 019 18



MULTIFUNCTION SLEEVE - VERTICAL - FOR 3 ROWS CABINETS

Pack (number of units)	1
Volume (dm³)	13,009
Weight (g)	1 718,00

Product characteristics

Multifunction sleeves

- Supplied with hinges connecting the cover to the back of the cabinet
- For use with 12 and 18-module cabinets using joining kit Cat.No 0 019 67
- Can be fitted with control units and accessories: P17 16 A and 32 A sockets with standard fixing centres, flush-mounted IP 55 Plexo wiring accessories, Osmoz, modular rail at the back of the box

Vertical

- For 3 rows cabinets

General characteristics

Plexo³ - IP 65 weatherproof cabinets, multifunction sleeves and accessories

- Self-extinguishing: resistance to incandescent wire 650°C.
- Allows to achieve assemblies conform to IEC 61 439 - 3
- Weatherproof cabinets - IP 65 - IK 09 - Class II
- Door and cabinet fully reversible. Removable chassis and faceplates from 2-row versions up
- 2-position rail for modular products and moulded cases. Spacing between rails 150 mm
- Can be fitted with perforated plates and solid faceplates for mounting non-modular products
- Lockable door handle, sealable cover and faceplate
- Shock-resistant polystyrene material
- Box colour light grey L750A, cover colour dark grey R746A
- Supplied without terminal blocks

Documentation

Catalogue pages & additional information

- Description page (p.286)
- Technical page (p.287)

Agreements & certificates of conformity

- OC / CB-654748

Installation & technical data

- EXB14046_CA_Plexo3_EN_print

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.