Specifications

Eaton 302407



Catalog Number: 302407

Eaton xEnergy Basic LV systems Low voltage switchgear. Surface-mounted installation distributor IP55, EP, WxHxD=1350x1460x270mm, white, swivel lever

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic empty enclosure	302407
EAN	**Product Length/Depth**
9010238160415	270 mm
Product Height	**Product Width**
1460 mm	1350 mm
Product Weight	**Compliances**
60.7 kg	RoHS conform

Powering Business Worldwide

Product specifications

Type

Basic device

Features

EMC-version

Connectable

Mounting plate depth-adjustable

Fitted with:

Door

Surface finishing

Powder coating

Degree of protection

IK10

IP55

Other

Grade material

Sheet steel

Material quality

Other

Color

White

Permissible load of the mounting plate according to IEC 62208 - max

0 N

Number of locks

0

RAL-number

9016

Material

Sheet steel

Steel

Mounting method

Wall fastening

Surface mounting

Functions

Basic device

Installation type

Floor standing wall model

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Drawings

eaton-low-voltage-switch-gear-dimensions-1230dim-437.eps

mCAD model

bpm_o_1350_14_p_ep_w.stp

bpm_o_1350_14_p_ep_w.dwg

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Number of covers/doors

2

Suitable for

Metrical mounting

Permissible load of the enclosure according to IEC 62208 - max

0 N

Permissible load of the door(s) according to IEC 62208 - max

0 N

Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890

0 W

Number of connector holes

0

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia