CAUTION The probe cable is a sensitive part of the probe and, therefore, you should be careful not to damage it through excessive bending or pulling. Avoid any mechanical shocks to the product to guarantee accurate performance and protection. Do not use the probe assembly if the red wear indicator in the cable has become visible.

WARNING Some of the probe tips / accessories are very sharp. You should handle these with care to avoid personal injury.

WARNING Use only Grounded instruments. Do not connect the probe's ground lead to a potential other than earth ground. Always make sure that the probe and oscilloscope are grounded properly.

WARNING Connect the probe to the oscilloscope and connect the ground lead to earth ground before connecting the probe to the circuit under test. Disconnect the probe input and the probe ground lead from the circuit under test before disconnecting the probe from the oscilloscope.

WARNING Indoor Use Only. Do not operate in wet / damp environments. Keep product surfaces dry and clean.

WARNING Do not operate in an explosive environment.

Safety and Regulatory Information

CSA is the Canadian certification mark to demonstrate compliance with the Safety requirements.

The CE mark is a registered trademark of the European Community. ISM GRP 1-A denotes the instrument is an Industrial Scientific and Medical Group 1 Class A product. ICES/NMB-001 indicates product compliance with the Canadian Interference-Causing Equipment Standard.

This symbol indicates the Environmental Protection Use Period (EPUP) for the product's toxic substances for the China RoHS requirements.

CAT II — IEC Measurement category II is for measurements performed on circuits directly connected to the low voltage installation. Example. Household appliances portable tools, and similar equipment.

NOTE If your probe requires cleaning, disconnect it from the instrument and clean it with mild detergent and water. Make sure the probe is completely dry before connecting it to the instrument.

© Keysight Technologies 2016
N2140-92000, July 2016,
Printed in USA

N2140-92000

Keysight N2140A and N2142A Passive Probes

Quick Start Guide



KEYSIGHT TECHNOLOGIES

⚠ The Keysight N2140A 200 MHz and N2142A 75 MHz passive probes are high impedance probes with switchable attenuation ratio (1:1 and 10:1). These are compatible with the Keysight InfiniiVision EDUX1002A/G and DSOX1102A/G digital storage oscilloscopes or similar oscilloscopes with 1 Mohm BNC input.

NOTE The BNC connector of these probes has a pin hole without a pin. This is as per the design and does not indicate any damage or fault in the probe.



Table 1 - Probe and its Supplied Accessories

ID	Part	Quantity	
		For N2140A	For N2142A
①	Passive probe	2	2
②	Ground Spring	2	-
③	Ground Lead	2	2
④	Adjustment Tool	1	1
⑤	Hook Tip	2	2
⑥	Protective Cap	1	1
⑦	Channel Identification rings	2 sets of each color with two rings in each set	

These accessories are provided in the N2141A kit for the N2140A probe and the N2143A kit for the N2142A probe.

These probes have been designed and calibrated for use with instruments having an input impedance of 1M Ω paralleled by 20pF. However, these may be recalibrated for use with instruments having an input capacitance of 15 to 40pF.

Adjusting Probes for Low-Frequency (LF) Compensation

The probe should be adjusted for LF compensation when it is connected to an oscilloscope input for the first time. LF compensation matches the probe cable capacitance to the oscilloscope input capacitance. This matching assures good amplitude accuracy from DC to the upper bandwidth limit frequencies. A poorly compensated probe clearly influences the overall system performance (probe and oscilloscope) and introduces measurement errors resulting in inaccurate readings and distorted waveforms.

To perform LF compensation:

1 Connect the probe to the oscilloscope's front-panel calibration output (a square wave label is usually seen near this output).

2 Use the supplied adjustment tool to adjust the LF compensation to an optimum square wave response as shown in the figure below.



Table 2 - Electrical Characteristics

Characteristic	Value	
Attenuation Ratio	1:1 / 10:1	
Input Capacitance	1:1 - 100pf	10:1 - 15pf
Compensation range (when terminated into 1 Mohm)	15pf - 40pf	
Input Resistance	1:1 - 1MΩ	10:1 - 10MΩ
Maximum Input Voltage	1:1 - 150V rms CAT II 10:1 - 300V rms CAT II	
⚠ Current Rating (DC, 1:1, & maximum voltage)	0.15mA	
Bandwidth	For N2140A 1:1 - 6 MHz 10:1 - 200 MHz	For N2142A 1:1 - 6 MHz 10:1 - 75 MHz

Table 3 - Physical & Environmental Characteristics

Characteristic	Value
Probe Body	95mm
Cable Length	1200mm
Weight	55g
Temperature	-10 °C to +55 °C (Operating) -40 °C to +70 °C (Non-operating)
Altitude	3,000 m (9,842 ft) (Operating) 12200 m (40,026 ft) (Non-operating)
Humidity	5% to 95% RH up to 30 °C (Operating) 5% to 65% RH above 30 °C up to 55 °C