Date: 12/04/2023

OLS-C01, G 3/8", Closed in media (SPST n.o.), Cable PVC 5 meter

OLS-C01, G 3/8", Closed in media (SPST n.o.), Cable PVC 5 meter

Item number: 57393756

Quantity: 1 pcs.

Order code: OLS-C01-G2Z-HNOK4-M0005-ZZZ W101OLS1Z1LC

Overview:
OLS-C01, G 3/8", Closed in media (SPST n.o.), Cable PVC 5 meter
Optoelectronic level switch for industrial applications
Model: OLS-C01
Process connection: G 3/8"
Output Signal: one switching output (PNP)
Switch function: Closed in media (SPST n.o.)
Power supply: 12 - 32 V DC
Electrical connection: Cable PVC
pin assignment el. connection: BN=U+, WH=U-, GN=SP
Unit cable length: meter
Cable length: 5
Operating pressure: max. 25 bar
Permissible medium temperature: -30…100 °C
Wetted parts: Stainless steel 1.4305, borosilicate glass, silicone adhesive
Specifications according to data sheet: LM 31.31

Details:
OLS-C01, G 3/8", Closed in media (SPST n.o.), Cable PVC 5 meter
Optoelectronic level switch for industrial applications
Model: OLS-C01
Process connection: G 3/8"
Output Signal: one switching output (PNP)
Switch function: Closed in media (SPST n.o.)
Power supply: 12 - 32 V DC
Electrical connection: Cable PVC
pin assignment el. connection: BN=U+, WH=U-, GN=SP
Unit cable length: meter
Cable length: 5
Operating pressure: max. 25 bar
Permissible medium temperature: -30…100 °C
Wetted parts: Stainless steel 1.4305, borosilicate glass, silicone adhesive
Specifications according to data sheet: LM 31.31

© 2023 - WIKA Instruments s.a.r.l.