Date: 11/04/2023

PSD-4; 0...1.6 bar abs ; two switching output (PNP/NPN) + 0...10 V

PSD-4; 0...1.6 bar abs ; two switching output (PNP/NPN) + 0...10 V

Item number: 48782351

Quantity: 1 pcs.

Order code: PSD-4-DZ-BA316-HDLZ-WZ-ZZ W1011PS4Z-SZAB-P-GSFI

Overview:
PSD-4; 0...1.6 bar abs ; two switching output (PNP/NPN) + 0...10 V
Electronic pressure switch with display
Output signal: two switching output (PNP/NPN) + 0...10 V
IO-Link: without
Power supply: 15...35 V DC
Measuring range: 0...1.6 bar abs
Process connection: G 1/4 A DIN EN ISO 1179-2
Sealing: FPM/FKM
Media temperature: -20 … 85 °C (-4 ... +185 °F)
El. connection: Circular connector M12x1 (5-pin)
pin assignment el. connection: U+=1, U-=3, S+=5, SP1=4, SP2=2
Accuracy: ± 0.5% of span
Approvals: without
with test protocol
Specifications according to data sheet: PE 81.86

Details:
PSD-4; 0...1.6 bar abs ; two switching output (PNP/NPN) + 0...10 V
Electronic pressure switch with display
Output signal: two switching output (PNP/NPN) + 0...10 V
IO-Link: without
Power supply: 15...35 V DC
Measuring range: 0...1.6 bar abs
Process connection: G 1/4 A DIN EN ISO 1179-2
Sealing: FPM/FKM
Media temperature: -20 … 85 °C (-4 ... +185 °F)
El. connection: Circular connector M12x1 (5-pin)
pin assignment el. connection: U+=1, U-=3, S+=5, SP1=4, SP2=2
Accuracy: ± 0.5% of span
Approvals: without
with test protocol
Specifications according to data sheet: PE 81.86

© 2023 - WIKA Instruments s.a.r.l.