Date: 11/04/2023

TG54.063/S, LM, 0...160°C , L1=80 mmx6mm

Model: TG54.063

Item number:	48776103
Quantity:	1 pcs.
Order code:	TG54.063LM-S-C1KZ-ND-B0080GZ-ZAHA1ZZ TO F-1IO-AZ1ZZZZZ2ZZZZ CERT22-EF2T-CA- - - - - - - - - - -
Overview:	TG54.063/S, LM, 0...160°C , L1=80 mmx6mm Process connection: 1/2 NPT flat instrument glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Ingress protection: IP 65 Permissible ambient temperature: -40 ... +100 °C *WIKA* with Serial number Test report 2.2 per EN 10204 Certificate Language: English and French Certificate for: thermometer mechanical Accuracy certificate: Certification of class and accuracy
Details:	Model: TG54.063 Specifications according to data sheet: TM 54.02 Accuracy class: class 1 per EN 13190 Nominal size: 063 Connection location: lower mount Connection design: standard, male thread Process connection: 1/2 NPT Scale range: 0 °C ... 160 °C Stem diameter: 6 mm Insertion length L1: 80 mm Window: flat instrument glass Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Ingress protection: IP 65 Permissible ambient temperature: -40 ... +100 °C with Serial number Manufacturer logo: *WIKA* Test report 2.2 per EN 10204 Certificate Language: English and French Certificate for: thermometer mechanical Accuracy certificate: Certification of class and accuracy

© 2023 - WIKA Instruments s.a.r.l.