TERMINAL BOX, 120X122X56, NO MP, POLYCARBONATE, IP66

CATALOG NUMBER

DPCP121206GE



The polycarbonate terminal box range, DPCP, with a IP 66, 67 protection degree, is available off the shelf in many different sizes. The DPCP range is well suited for indoor and outdoor environments, even in locations where there is direct sunlight, thanks to the resistance to UV radiation. Water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that, unnecessary downtime.

INDUSTRY STANDARDS

CE
UKCA
GOST
IP

FEATURES

Description: Polycarbonate box, halogen-free, suitable for outdoor use. High UV radiation resistance. Self-extinguishing.
Material: Polycarbonate.
Gasket: Polyurethane gasket integrated in the box cover.
Temperature resistance: -40 °C to +80 °C.
Flammability: UL746C 5V.
Protection: IP 66, 67 | IK 08 (-25 °C … +35 °C).
Finish: RAL 7035.
Approvals: CE, GOST. For cULus_UL Listed approvals, please contact our sales department.
Delivery: Body, cover, cover screws manufactured from stainless steel, mounting screws and cover plugs made of polyamide.
Flammability: UL746C 5V
Protection: IP 66, 67 | IK 08 (-25 °C … +35 °C)
Delivery: Body, cover, cover screws manufactured from stainless steel, mounting screws and cover plugs made of polyamide

PRODUCT ATTRIBUTES

Height: 120 mm
Width: 122 mm
Depth: 56 mm
Max Mounting Depth: 42 mm
Weight: 0.2 kg
Material: Polycarbonate
Finish: Smooth

Color: Light Gray

Color Code: RAL 7035

ADDITIONAL PRODUCT DETAILS

Note: Terminal box, with transparent cover fitted, can be ordered by replacing GE with TE in the item number.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.