Date: 11/04/2023

S73.100/4, -200...+50°C, L1=465x6mm,

Gas actuated thermometer, stainless steel series

Item number:	48683713
Quantity:	1 pcs.
Order code:	S73.100-CNA-4ND-B0465-ZZZ-Z-Z-HZZ-ZZZZZZ G5 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	S73.100/4, -200...+50°C, L1=465x6mm, 1/2 NPT axial laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °C Scale range: -200 °C ... +50 °C Connection design: 4, compression fitting, sliding on stem Process connection: 1/2 NPT Stem diameter: 6 mm Insertion length L1: 465 Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.