Specifications

Eaton 80D125



Catalog Number: 80D125

Eaton Bussmann series low voltage D fuse, 500V, 80A, Non Indicating, fuse, Class C gL/gG, Time delay, Silver, Ceramic body

General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
80D125

EAN
5027590490429

UPC
051712837989

Product Length/Depth
60 mm

Product Height
33 mm

Product Width
33 mm

Product Weight
106 g

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269
VDE
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

fuse

Application

For domestic and general industrial applications

Amperage Rating

80 A

Fuse size

DIV

Breaking capacity

50 kA

Construction size (fuse inserts)

DIV

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

D125 - Time delay

Accessory/spare part type

80GD125 Silver screw cap gauge piece

Utilization category

gL/gG (cable protection/equipment protection)

Color

Silver

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D4

Construction size

DIV

Fuse shape

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

UKCA Bottle fuse-links, holders, carriers and accessories

CE Bottle fuse-links, holders, carriers and accessories

Bottle

Response time

Time-delay

Suitable for

R1 1/4" / DIV Fuse base

Material

White ceramic body

Release characteristic

Time-lag

Quantity

10

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia