Date: 22/04/2024

PCS2PC 20 … 220 bar 1/4 NPT-F, Adaptor M20x1,5-F

Compact Pressure Switch

Item number: 48796508

Quantity: 1 pcs.

Order code: PCS2PC-BAQB-1ISZZZ1ZZ ZCKW
F4-C1- - - - -

Overview:
PCS2PC 20 … 220 bar 1/4 NPT-F, Adaptor M20x1,5-F
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, gold-plated contact, hermetically sealed with argon gas
Setting range, working range, proof pressure: 20 … 220 bar, working range 0 … 350 bar, proof pressure 500 bar
Set point definition: Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

Approvals / Certificates
IECEx-ATEX Ex ia

Details:
Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
1xSPDT, gold-plated contact, hermetically sealed with argon gas
20 … 220 bar, working range 0 … 350 bar, proof pressure 500 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Switch standard: without
Brand: WIKA Instruments Italia

© 2024 - WIKA Instruments s.a.r.l.

Ingress Protection: IP66
PCS2PC 20 … 220 bar
Approvals / Certificates
IECEx-ATEX Ex ia

© 2024 - WIKA Instruments s.a.r.l.