Date: 22/04/2024

PCS2VG -1 … -0,2 bar Adaptor G 1/2 A-M, Cable gland non-armoured, stainless steel (AISI 304)

Compact Pressure Switch

Item number:	48791920
Quantity:	1 pcs.
Order code:	PCS2VG-BAAB-47SZZZZZZ ZCKW
Overview:	PCS2VG -1 … -0,2 bar Adaptor G 1/2 A-M, Cable gland non-armoured, stainless steel (AISI 304) Compact Pressure Switch PCS switch enclosure: aluminium,copper-free Measuring elements and wetted parts: Diaphragm NBR Connection: Stainless steel AISI 316L contact version: 1xDPDT, silver contact Setting range, working range, proof pressure: -1 … -0,2 bar, working range -1 … 6 bar, proof pressure 10 bar Set point definition: Set Point not defined Process connection: Adaptor G 1/2 A-M Electrical connection: Cable gland non-armoured, stainless steel (AISI 304) standard direct or wall mounting, fixing bore on the case Ingress Protection: IP66 Brand: WIKA Instruments Italia Specifications according to data sheet: PV 33.30 Repeatability of set point: ≤ 1% of end of setting range
Details:	Compact Pressure Switch Model PCS Specifications according to data sheet: PV 33.30 Repeatability of set point: ≤ 1% of end of setting range switch enclosure: aluminium,copper-free Measuring elements and wetted parts: Diaphragm NBR 1xDPDT, silver contact -1 … -0,2 bar, working range -1 … 6 bar, proof pressure 10 bar Set Point not defined Process connection: Adaptor G 1/2 A-M Electrical connection: Cable gland non-armoured, stainless steel (AISI 304) standard direct or wall mounting, fixing bore on the case Approvals / Certificates: without Switch standard: without Brand: WIKA Instruments Italia Ingress Protection: IP66 PCS2VG -1 … -0,2 bar

© 2024 - WIKA Instruments s.a.r.l.