Specifications

Eaton 286721



Catalog Number: 286721

Eaton xEnergy Basic LV systems Low voltage switchgear. Sheet steel door with rotary door handle HxW=1200x600mm

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	286721
EAN	**Product Length/Depth**
4015082867218	45 mm
Product Height	**Product Width**
1210 mm	615 mm
Product Weight	**Compliances**
6.7 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Wall-mounting distribution system
Service distribution board IVS
Accessory
Accessory consideration

Special features

Closed
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
1-point long with three-point turn-lock

Type

Additional equipment for wall-mounted service distribution board IVS

Accessory/spare part type

Doors

Surface finishing

With powder coating
Powder coating

Color

Light gray (RAL 7035)
Gray

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

1260 mm

Suitable for width

600 mm

Cover/door type

Three-point turn-lock

Material

Sheet steel
Steel

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_xEnergy_Basic_BP

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Housing material

Sheet steel

Model

Stop door

Mounting method

Surface mounting

Functions

Wall-mounting distribution system

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia