Specifications

Eaton 171367



Catalog Number: 171367

Eaton Moeller® series SL4 Strobe light module, blue, LED, 230 V

General specifications

Product Name
Eaton Moeller® series SL4 Strobe light module

Catalog Number
171367

EAN
4015081678983

Product Length/Depth
43 mm

Product Height
75 mm

Product Width
43 mm

Product Weight
0.044 kg

Certifications
CSA-C22.2 No. 94-91
IEC/EN 60529
UL 508
UL File No.: E29184
CSA Class No.: NKCR7
CE
UL report applies to both US and Canada
IEC/EN 60947-5-1
CSA-C22.2 No. 14-10
Certified by UL for use in Canada
UL Category Control No.: NKCR
UL

Powering Business Worldwide

Features & Functions

Color

Blue

Enclosure color

Black

Functions

Flash light

Light modules

LED

Number of modules

Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base)

General

Connection to SmartWire-DT

No

Current consumption

20 mA at 230/240 V AC

Degree of protection

NEMA 13

IP66

Flashing frequency

1.4 Hz

Lifespan, electrical

100,000 h

Light type

Strobe light

Material

Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC)

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

SL signal towers

Radiation angle

360 °

Rated impulse withstand voltage (Uimp)

4000 V AC

Shock resistance

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Type

Strobe light module

Voltage type

AC

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Electrical rating

Leakage current

0.003 A

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - min

230 V

Rated operational voltage (Ue) at AC - max

240 V

Rated operational voltage (Ue) at DC - min

0 V

Rated operational voltage (Ue) at DC - max

0 V

Resources

Brochures

SL4, SL7, SLC Stack light overview brochure BR047017

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Declarations of conformity

DA-DC-00004257.pdf

DA-DC-00004253.pdf

Drawings

eaton-operating-sl4-continuous-light-dimensions.eps

eaton-operating-button-sl7-continuous-light-symbol-005.eps

eaton-operating-sl7-strobe-light-module-symbol.eps

eCAD model

ETN.171367.edz

Installation instructions

IL047001ZU

Installation videos

Signal towers SL4 and SL7

mCAD model

DA-CD-sl4_bfl4

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia