Date: 22/01/2024

233.50.063 40 bar G1/4B lower mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number: 9020799

Quantity: 1 pcs.

Order code: 233.50-C-BG440Z-GB-UZEZCZZ-ZZZZZZZ 313D4AZIYG0 Z2Z-IZZZZZZ121ZZ
LABEL-PG1DE-ZZZZZ

Overview:
233.50.063 40 bar G1/4B lower mount
Measuring System 316 SS
Ingress protection: IP 65
class 1.6
Window: polycarbonate
Case filling fluid: glycerine
Permissible ambient temperature: -20 … +60 °C
Permissible medium temperature: + 100 °C
Pressure Gauge Standard: International (standard Europe)
stop-pin at zero *WIKA*
with Serial number
Label: WIKA standard without / with Tag-number

Details:
Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 233.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: with
Nominal size: 063 mm
Scale range: 0...40 bar
Process connection: G 1/4 B
Connector location: lower mount
Window: polycarbonate
Pointer: standard pointer
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: glycerine
Ingress protection: IP 65
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)

© 2024 - WIKA Instruments s.a.r.l.

Date: 22/01/2024

Manufacturer logo: *WIKA*
with Serial number
stop pin on dial: at zero

© 2024 - WIKA Instruments s.a.r.l.