efector100

IIS206

IIKC015BASKG/M/US-104-DRS/2LED

Inductive sensors



Product characteristics		
Inductive sensor		
Metal thread M30 x 1.5		
Connector		
Operation as 3-wire or 2-wire possible		
Increased sensing range		
Optical setting aid (2 LED)		
Gold-plated contacts		
Sensing range 15 mm; [f] flush mountable		
Electrical data		
Electrical design		3-wire DC PNP; 2-wire DC PNP/NPN
Operating voltage	[V]	10...36 DC
Current consumption	[mA]	10 (24 V)
Protection class		II
Reverse polarity protection		yes
Outputs		
Output function		normally open
Voltage drop	[V]	< 2.5
Minimum load current	[mA]	2; only in 2-wire operation
Leakage current	[mA]	< 0.5; only in 2-wire operation
Current rating	[mA]	100
Short-circuit protection		pulsed
Overload protection		yes
Switching frequency	[Hz]	100
Range		
Sensing range	[mm]	15
Real sensing range (Sr)	[mm]	15 ± 10 %
Operating distance	[mm]	0...12.1
Accuracy / deviations		
Correction factors		mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis	[% of Sr]	3...15
Switch-point drift	[% of Sr]	-10...10
Environment		
Ambient temperature	[°C]	-25...70
Protection		IP 67
Tests / approvals		

EMC	EN 61000-4-2 ESD: EN 61000-4-3 HF radiated: EN 61000-4-4 Burst: EN 61000-4-6 HF conducted: EN 55011:	4 kV CD / 8 kV AD 10 V/m 2 kV 10 V class B
MTTF [Years]		1475

Mechanical data

Mounting		flush mountable
Housing materials		Brass white bronze coated; active face: PBT
Weight	[kg]	0.14

Displays / operating elements

Output status indication	LED	yellow (4 x 90°)
Setting aid	LED	Red

Electrical connection

Connection		M12 connector; Gold-plated contacts

Wiring







Accessories

Accessories (included)		2 lock nuts

Remarks

Remarks		suitable for PLC type 1 according to IEC 61131-2
Pack quantity	[piece]	1