PRODUCT-DETAILS

OT250KFCC3T

OT250KFCC3T Safety switch



General Information

Extended Product Type	OT250KFCC3T
Product ID	1SCA022276R8830
EAN	6417019063256
Catalog Description	OT250KFCC3T Safety switch
Long Description	Safety switch, 3-p. 415V AC23 250A, 132kW. Mounted auxiliary contact: 2NO1NC. Plastic enclosure. IP65. Black Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. PE terminals included.

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Declaration	1SCC340075D0201

© 2025 ABB. All rights reserved.

RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	17fd61fa-5bdf-405f-b479-6e410e31a63d Finland
Simplified SCIP	edb7c5ed-91ee-4879-89c3-4ed40ae8612d Germany 89e8acd3-33b3-47c9-a760-d594a45a87f0 Poland 3c5fa5fe-de7b-4097-b6e7-4997cdb53b6f Spain bfa28274-3760-47c5-b5c3-58198103767b Belgium 73a6b23e-2bda-4e2d-ae99-d43b4475548a Hungary 134c6c9d-d707-4666-b9e8-7ab570805edf Poland 695c241d-f03b-4275-a985-81f056907fc6 Bulgaria 0f93d6a4-3124-4cfa-87de-34ab2bcf25f5 Greece b9d0e652-f8fc-43fe-98fa-8b52f8e2dda0 Portugal 774c123d-5677-40ff-ba69-333482efe3d2 Sweden 5d8c58f4-80c6-4c1e-8ef0-279c721b51ba Estonia a9fbefe5-60c4-4f68-8d47-6e21060684d5 Hungary 9f523786-1992-473b-b53d-ef1ef9419772 Poland b606eca1-d121-404b-a86b-22c72a4806bf France c3c0839b-1bfb-4b18-8703-1c332424df3d Czech Republic aa889c2e-4237-4b3d-b1e9-573b0be57f32 Germany 2e4f4b04-9f29-4f06-8101-dc82edc8fced France b010d8f4-a301-43af-8e70-ae3af9f57e18 Germany 56d30019-d24c-4085-a8a7-341f0ed01bd3 Netherlands e7921484-446d-41bc-8953-fdf9f36b5dc2 Sweden b8387355-0060-4a9f-ab74-1877b666ed24 Italy e009dfcc-8e26-4c43-9277-6dfaff613950 Germany e7eaad53-84bd-4943-8425-62c4ca58881a Croatia 17114208-0521-4ef0-b305-36d676a0e0bc Belgium 73218bb2-51d6-4f4d-ba28-26dcb446bd93 Norway b0719754-1cdd-40cc-b945-bde7b8128211 Denmark 1bc80046-df67-4507-8a47-f1dfd7d3162a Germany
Toxic Substances Control Act - TSCA	1SCC340095D0201

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340015M0004

Environmental

Degree of Protection	acc. to IEC 60529 IP65
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country or Territory of Origin	Finland

Dimensions

Product Net Width	280 mm
Product Net Height	560 mm
Product Net Depth / Length	130 mm
Product Net Weight	7.063 kg

© 2025 ABB. All rights reserved.

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	415 mm
Package Level 1 Depth / Length	710 mm
Package Level 1 Height	325 mm
Package Level 1 Gross Weight	9.3 kg
Package Level 1 EAN	6417019063256

Technical

Cable Entry Position	Top/Bottom
Cable Outlets Per Side	II-flange / II-flange
Color	RAL7035
Connecting Capacity Main Circuit	Hole Diameter 8 mm Screw Clamp / PE Terminal 2pc,10 ... 70 mm^2
Conventional Thermal Current (I_{the})	Fully Enclosed 250 A
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Handle Color	Black
Handle Type	Pistol handle
Impact Resistance Rating	Housing IK08
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	2 NO, 1 NC
Neutral Type	No Neutral Terminal
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	2
Number of Poles	3P
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Rated Conditional Short-Circuit Current (I_{nc})	40.5 kA
Rated Insulation Voltage (U_i)	750 V
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 132 kW (500 V) 160 kW (690 V) 200 kW
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 30 kA
Rated Short-time	for 1 s 8 kA

© 2025 ABB. All rights reserved.

Withstand Current Low Voltage (I_{cw})	
Recommended Screw Driver	Main Circuit M8
Standards	IEC 60947-1, -3
Tightening Torque	Main Circuit 22 N·m

Technical UL/CSA

Recommended Screw Driver	Main Circuit M8
Tightening Torque	Main Circuit 22 N·m

Certificates and Declarations

Declaration of Conformity - CE	1SCC340025D2704

External Classifications and Standards

Object Classification Code	Q
ETIM 9	EC000216 - Switch disconnector (low voltage)
ETIM 10	EC000216 - Switch disconnector (AC)
UNSPSC	39122205
IDEA Granular Category Code (IGCC)	5166 >> Safety switch
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3642406
E-Number (Norway)	1429308
E-Number (Sweden)	3140230

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

© 2025 ABB. All rights reserved.





© 2025 ABB. All rights reserved.